

KERN CCS 10K-6

Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Approval

CE mark ✓

Display

Display type LCD
 Display backlight ✓
 Display digit height 20 mm

Construction

Dimensions weighing platform (W×D×H) 300×240×105 mm
 Dimensions completely mounted (W×D×H) 320×330×125 mm
 Material housing plastic
 Material weighing plate stainless steel
 Dimensions weighing surface (W×D) 300×240 mm
 Cable length 1,5 m
 Display device cable length 3 m
 Material load cell(s) aluminium
 Levelling feet adjustable ✓

Functions

Auto-off interval(s) in mains power mode 5 min
 30 min
 15 min
 Auto-off interval(s) in battery mode/rechargeable battery mode selectable
 PreTare function ✓
 Tare function manual (multi)
 Counting function ✓
 Tolerance weighing ✓
 Conversion function ✓
 Recipe/summing level Sum A
 PLU - total 100
 Sum memory function ✓
 Memory function ✓
 Interfaces RS-232 standard
 IP protection - display IP23
 IP protection - load cell IP65
 IP protection - platform IP65

Counting

Smallest piece weight when piece counting - laboratory conditions 5 mg
 Smallest piece weight when piece counting - normal conditions 50 mg

Category

Brand KERN
 Product category Industrial scale
 Product group Counting system
 Product family CCS

Measuring System

Reference scale - item number CFS 300-3
 Quantity scale - Item number KFP 15V20M
 Construction type of the scale Multi-range balance
 Weighing system Strain gauge
 Reference scale - Weighing capacity [Max] 0,3 kg
 Quantity scale - Weighing capacity [Max] 15 kg
 Reference scale - Readability [d] 1 mg
 Quantity scale - Readability [d] 0,0005 kg
 Linearity ±
 Reference scale - Linearity 4 mg
 Quantity scale - Linearity 0,0015 kg
 Reproducibility 0,000002 kg
 Reference scale - Reproducibility 2 mg
 Quantity scale - Reproducibility 0,0005 kg
 Default unit kg
 Units g
 Adjustment options Adjusting with external weight
 Recommended adjusting weight 15 kg (F1)
 Stabilization time 2 s
 Eccentric loading at 1/3 [Max] 0,000006 kg
 Reference scale - Eccentric loading at 1/3 [Max] 6 mg
 Quantity scale - Eccentric loading at 1/3 [Max] 0,0025 kg
 Loadcell type aluminum Alloy IP64

KERN CCS 10K-6

KERN

Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Counting reference weight can be entered	✓
Reference quantity	n (any number of pieces)
Counting resolution (laboratory conditions)	3.000.000

Power Supply

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	40 h
Rechargeable battery operating time - backlight off	60 h
Battery / accumulator type	Pb

Environmental conditions

Humidity of environment [Min]	0 %
Humidity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	630×535×350 mm
Net weight	6,9 kg
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	10 kg
Shipping weight	23,6 kg

Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/Max depends on resolution and capacity
Article number for DAkKS calibration	962-128-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

