# KERN CCS 150KO.1L



320×330×125 mm

stainless steel

650×500 mm

plastic

1,5 m

aluminium

3 m

Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS

Reference scale - item number  Quantity scale - Item number  TKFP 150V20LM-A  Construction type of the scale  Weighing system  Reference scale - Weighing capacity [Max]  Quantity scale - Weighing capacity [Max]  Reference scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Linearity  Reference scale - Linearity  Quantity scale - Linearity  Quantity scale - Linearity  Quantity scale - Linearity  Quantity scale - Reproducibility  Adjusting with external weight  Recommended adjusting weight  Stabilization time  2 s  Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]	Measuring System	
Construction type of the scale Weighing system Reference scale - Weighing capacity [Max] Quantity scale - Weighing capacity [Max] Reference scale - Readability [d] Quantity scale - Linearity Reference scale - Linearity Quantity scale - Linearity Quantity scale - Linearity Quantity scale - Reproducibility Recommended adjusting weight 150 kg (M1) Stabilization time 2 s Eccentric loading at 1/3 [Max] Quantity scale - Eccentric loading at 1/3 [Max]	Reference scale - item number	CFS 6K0.1
Weighing system Reference scale - Weighing capacity [Max]  Quantity scale - Weighing capacity [Max]  Reference scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Readability [d]  Linearity  Reference scale - Linearity  Quantity scale - Linearity  Quantity scale - Linearity  Quantity scale - Reproducibility  Adjustment options  Adjusting with external weight  Recommended adjusting weight  Stabilization time  2 s  Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]	Quantity scale - Item number	TKFP 150V20LM-A
Reference scale - Weighing capacity [Max]  Quantity scale - Weighing capacity [Max]  Reference scale - Readability [d] 100 mg  Quantity scale - Readability [d] 0,005 kg  Linearity ±  Reference scale - Linearity 200 mg  Quantity scale - Linearity 0,02 kg  Reproducibility 0,05 kg  Reference scale - Reproducibility 100 mg  Quantity scale - Reproducibility 0,005 kg  Reference scale - Reproducibility 0,005 kg  Default unit kg  Units kg  Units Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]	Construction type of the scale	Multi-range balance
capacity [Max]  Quantity scale - Weighing capacity [Max]  Reference scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Readability [d]  Quantity scale - Readability [d]  Linearity  Reference scale - Linearity  Quantity scale - Linearity  Quantity scale - Linearity  Quantity scale - Reproducibility  Adjusting with external weight  Recommended adjusting weight  Stabilization time  2 s  Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]	Weighing system	Strain gauge
[Max]  Reference scale - Readability [d] 100 mg  Quantity scale - Readability [d] 0,005 kg  Linearity ±  Reference scale - Linearity 200 mg  Quantity scale - Linearity 0,02 kg  Reproducibility 0,05 kg  Reference scale - Reproducibility 100 mg  Quantity scale - Reproducibility 0,005 kg  Default unit kg  Units kg  Units kg  Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max] 0,025 kg  Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg		6 kg
Quantity scale - Readability [d]0,005 kgLinearity±Reference scale - Linearity200 mgQuantity scale - Linearity0,02 kgReproducibility0,05 kgReference scale - Reproducibility100 mgQuantity scale - Reproducibility0,005 kgDefault unitkgUnitskgAdjustment optionsAdjusting with external weightRecommended adjusting weight150 kg (M1)Stabilization time2 sEccentric loading at 1/3 [Max]0,05 kgReference scale - Eccentric loading at 1/3 [Max]500 mgQuantity scale - Eccentric loading at 1/3 [Max]0,025 kg		150 kg
Linearity ±  Reference scale - Linearity 200 mg  Quantity scale - Linearity 0,02 kg  Reproducibility 0,05 kg  Reference scale - Reproducibility 100 mg  Quantity scale - Reproducibility 0,005 kg  Default unit kg  Units kg  Units kg  Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max] 0,025 kg  Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Reference scale - Readability [d]	100 mg
Reference scale - Linearity 200 mg  Quantity scale - Linearity 0,02 kg  Reproducibility 0,05 kg  Reference scale - Reproducibility 100 mg  Quantity scale - Reproducibility 0,005 kg  Default unit kg  Units kg  Units kg  Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max] 0,025 kg  Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Quantity scale - Readability [d]	0,005 kg
Quantity scale - Linearity       0,02 kg         Reproducibility       0,05 kg         Reference scale - Reproducibility       100 mg         Quantity scale - Reproducibility       0,005 kg         Default unit       kg         Units       kg         Ib       Adjusting with external weight         Recommended adjusting weight       150 kg (M1)         Stabilization time       2 s         Eccentric loading at 1/3 [Max]       0,05 kg         Reference scale - Eccentric loading at 1/3 [Max]       500 mg         Quantity scale - Eccentric loading at 1/3 [Max]       0,025 kg	Linearity	±
Reproducibility 0,05 kg Reference scale - Reproducibility 100 mg Quantity scale - Reproducibility 0,005 kg Default unit kg Units kg Units kg Adjustment options Adjusting with external weight Recommended adjusting weight 150 kg (M1) Stabilization time 2 s Eccentric loading at 1/3 [Max] 0,05 kg Reference scale - Eccentric loading at 1/3 [Max] 0,025 kg Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Reference scale - Linearity	200 mg
Reference scale - Reproducibility 100 mg  Quantity scale - Reproducibility 0,005 kg  Default unit kg  Units kg  Ib  Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max] 500 mg  Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Quantity scale - Linearity	0,02 kg
Quantity scale - Reproducibility       0,005 kg         Default unit       kg         Units       kg lb         Adjustment options       Adjusting with external weight         Recommended adjusting weight       150 kg (M1)         Stabilization time       2 s         Eccentric loading at 1/3 [Max]       0,05 kg         Reference scale - Eccentric loading at 1/3 [Max]       500 mg         Quantity scale - Eccentric loading at 1/3 [Max]       0,025 kg	Reproducibility	0,05 kg
Default unit kg Units kg Ib  Adjustment options Adjusting with external weight Recommended adjusting weight 150 kg (M1) Stabilization time 2 s Eccentric loading at 1/3 [Max] 0,05 kg Reference scale - Eccentric loading at 1/3 [Max] Quantity scale - Eccentric loading at 1/3 [Max] O,025 kg	Reference scale - Reproducibility	100 mg
Units kg lb  Adjustment options Adjusting with external weight  Recommended adjusting weight 150 kg (M1)  Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]	Quantity scale - Reproducibility	0,005 kg
Adjustment options Adjusting with external weight Recommended adjusting weight 150 kg (M1) Stabilization time 2 s Eccentric loading at 1/3 [Max] 0,05 kg Reference scale - Eccentric loading at 1/3 [Max] Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Default unit	kg
Recommended adjusting weight  Recommended adjusting weight  Stabilization time  2 s  Eccentric loading at 1/3 [Max]  Reference scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  O,025 kg	Units	_
Stabilization time 2 s  Eccentric loading at 1/3 [Max] 0,05 kg  Reference scale - Eccentric loading at 1/3 [Max] 500 mg  at 1/3 [Max] 0,025 kg	Adjustment options	, ,
Eccentric loading at 1/3 [Max] 0,05 kg Reference scale - Eccentric loading at 1/3 [Max] 500 mg  Quantity scale - Eccentric loading at 1/3 [Max] 0,025 kg	Recommended adjusting weight	150 kg (M1)
Reference scale - Eccentric loading at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  0,025 kg	Stabilization time	2 s
at 1/3 [Max]  Quantity scale - Eccentric loading at 1/3 [Max]  0,025 kg	Eccentric loading at 1/3 [Max]	0,05 kg
at 1/3 [Max]	_	500 mg
Loadcell type aluminum Alloy IP64		0,025 kg
	Loadcell type	aluminum Alloy IP64

Approval	
CE mark	✓
Display	
Display type	LCD
Display backlight	✓
Display digit height	20 mm
Construction	
Dimensions weighing platform (W×D×H)	650×500×136 mm

Dimensions completely mounted

 $(W \times D \times H)$ 

(W×D) Cable length

Counting

Material housing

Material weighing plate

Dimensions weighing surface

Display device cable length

Material load cell(s)

Levelling feet adjustable

Functions	
Functions	
Number of keys for operation	20
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
PreTare function	✓
Tare function	manual (multi)
Counting function	✓
Tolerance weighing	✓
Conversion function	✓
Recipe/summing level	Sum A
PLU - total	100
Sum memory function	✓
Memory function	✓
Interfaces	RS-232 standard
IP protection - display	IP23
IP protection - load cell	IP65
IP protection - platform	IP65

Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Counting reference weight can be entered	✓

1

## KERN CCS 150KO.1L



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Reference quantity n (any number of pieces)

Counting resolution (laboratory conditions)

1.500.000

**Power Supply** Input voltage power supply / 220 V - 240 V AC, 50 Hz power [Max] Input voltage device / power [Max] 12 V, 500 mA Plug-in power supply type Power adapter Supplied power supply Power supply unit Plug-in power supply / adapter for UK countries - included with the US delivery CH **EURO** Plug-in power supply / adapter for UK countries - optional US CH Rechargeable battery optional Rchrg. battery optional Rechargeable battery charging 12 h Rechargeable battery operating 70 h time - backlight on Rechargeable battery operating 60 h

Environmental conditions	
Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

time - backlight off

Packing & Shipping	
Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	720×580×410 mm
Net weight	23,2 kg
Shipping method	Parcel service
Net weight approx.	24 kg
Gross weight approx.	28 kg
Shipping weight	34,2 kg

Services (optional)	
Article number for adjustment at the location of installation	abhängig von Auflösung/ Max   depends on resolution and capacity
Article number for DAkkS calibration	962-129-128

Article number for certificate of conformity (verification) 969-517

## **Pictograms**

### **STANDARD**



#### OPTION

