
KERN CCS 1T-1L



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS
Measuring System	
Reference scale - item number	CFS 6K0.1
Quantity scale - Item number	KFP 1500V20NM
Construction type of the scale	Multi-range balance
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	6 kg
Quantity scale - Weighing capacity [Max]	1500 kg
Reference scale - Readability [d]	100 mg
Quantity scale - Readability [d]	0,5 kg
Linearity	±
Reference scale - Linearity	200 mg
Quantity scale - Linearity	0,5 kg
Reproducibility	0,0002 kg
Reference scale - Reproducibility	100 mg
Quantity scale - Reproducibility	0,5 kg
Default unit	kg
Units	kg Ib
Adjustment options	Adjusting with external weight
Recommended adjusting weight	1500 kg (M1)
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,0005 kg
Reference scale - Eccentric loading at 1/3 [Max]	500 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,5 kg

Loadcell type	aluminum Alloy IP64
Approval	
CE mark	1
Display	
Display type	LCD
Display backlight	1
Display digit height	20 mm
Construction	
Dimensions weighing platform (W×D×H)	1500×1250×80 mm
Material housing	plastic
Material weighing plate	coated metal
Dimensions weighing surface (W×D)	1500×1250 mm
Cable length	1,5 m
Display device cable length	5 m
Material load cell(s)	aluminium
Levelling feet adjustable	\checkmark
Functions	
Number of keys for operation	20
Auto-off interval(s) in battery	
mode/rechargeable battery mode	selectable
mode/rechargeable battery mode PreTare function	selectable
PreTare function	✓
PreTare function Tare function	✓ manual (multi)
PreTare function Tare function Counting function	✓ manual (multi) ✓
PreTare function Tare function Counting function Tolerance weighing	✓ manual (multi) ✓ acoustically
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal	✓ manual (multi) ✓ ✓ acoustically visual
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function	✓ manual (multi) ✓ ✓ acoustically visual ✓
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level	✓ manual (multi) ✓ ✓ acoustically visual ✓ Sum A
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total	✓ manual (multi) ✓ ✓ acoustically visual ✓ Sum A 100
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function	✓ manual (multi) ✓ ✓ acoustically visual ✓ Sum A 100 ✓
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function	✓ manual (multi) ✓ acoustically visual ✓ Sum A 100 ✓
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Underfloor weighing	✓ manual (multi) ✓ acoustically visual ✓ Sum A 100 ✓ None
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Underfloor weighing Interfaces	✓ manual (multi) ✓ ✓ acoustically visual ✓ Sum A 100 ✓ ✓ None RS-232 standard
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Underfloor weighing Interfaces IP protection - display	 ✓ manual (multi) ✓ ✓ acoustically visual ✓ ✓ Sum A 100 ✓ ✓ None RS-232 standard IP23
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Memory function Underfloor weighing Interfaces IP protection - display IP protection - load cell	✓ manual (multi) ✓ acoustically visual ✓ Sum A 100 ✓ INONE RS-232 standard IP23 IP65
PreTare function Tare function Counting function Tolerance weighing Tolerance weighing - type of signal Conversion function Recipe/summing level PLU - total Sum memory function Memory function Underfloor weighing Interfaces IP protection - display IP protection - load cell IP protection - platform	✓ manual (multi) ✓ acoustically visual ✓ Sum A 100 ✓ INONE RS-232 standard IP23 IP65

KERN CCS 1T-1L



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Counting reference weight can be entered	1
Reference quantity	n (any number of pieces)
Counting resolution (laboratory conditions)	15.000.000
Power Supply	
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	70 h
Rechargeable battery operating time - backlight off	60 h
Battery / accumulator type	Pb
Environmental conditions	
Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	00 °C
Packing & Shipping	
Readability force [d] (N)	4 d
Dimensions packaging (W×D×H)	1250×1525×540 mm
Net weight	180 kg
Shipping method	Freight
Net weight approx.	180 kg

185 kg

185 kg

Gross weight approx.

Shipping weight

Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/ Max depends on resolution and capacity
Article number for DAkkS calibration	962-130-128
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



.

4 DAYS

OPTION

••	DAkkS
ACCU	+3 DAYS