

KERN CD 10-2P2

Loadcell made of stainless steel

KERN



Category

Brand	Sauter
Product category	Measuring cell
Product group	Load/force measuring cell
Product family	CD P2

Measuring System

Weighing capacity [Max]	10000 kg
Load cell connection	4-wire
Load cell OIML class	C2
Load cell - Resolution (verifiable)	2000 e
Load cell - characteristic value - nominal	1,5 mV/V
Load cell - characteristic value - variance	0,002 mV/V
Load cell - Y-value	5000
Load cell - Combined error	0,03%
Load cell - Dead load [Min] (%)	0%
Measuring applications	force mass
Load cell - Input resistance - nominal	700 Ω
Load cell - Output resistance - nominal	703 Ω
Load cell - Isolation resistance - [Min]	5000 MΩ
Load cell - Recommended excitation voltage [Min]	5 V
Load cell - Recommended excitation voltage [Max]	12 V
Load cell - Input resistance - variance	7 Ω

Load cell - Output resistance - variance

4 Ω

Measuring range force [Max] (N)

100 kN

Directions of force

tension
compression

Approval

CE mark



Construction

Design	Tension-/compression rod
Material	stainless steel
Cable length	20 m
Mounting - force application	External thread M36 × 3
Mounting - force dissipation	External thread M36 × 3

Functions

IP protection - complete device

IP68

Environmental conditions

Use temperature [Min]	-10 °C
Use temperature [Max]	40 °C
Ambient temperature [Min]	-35 °C
Ambient temperature [Max]	65 °C
Storage temperature [Min]	-40 °C
Storage temperature [Max]	70 °C

Packing & Shipping

Readability force [d] (N)	36 d
Dimensions packaging (W×D×H)	220×220×160 mm
Net weight	2,2 kg
Shipping method	Parcel service
Net weight approx.	2,2 kg
Gross weight approx.	2,8 kg
Shipping weight	2,7 kg

Services (optional)

Article number for factory calibration (tensile force)	961-166V
Article number for factory calibration (compressive force)	961-266V
Article number for factory calibration (tensile force/compressive force)	961-366V

KERN CD 10-2P2

Loadcell made of stainless steel

KERN

Pictograms

STANDARD



IP 68

OPTION



+4 DAYS