

KERN CR 5000-1Q1

KERN

Loadcell made of stainless steel



Category

| | |
|------------------|---------------------------|
| Brand | Sauter |
| Product category | Measuring cell |
| Product group | Load/force measuring cell |
| Product family | CR Q1 |

Measuring System

| | |
|--|---------------|
| Weighing capacity [Max] | 5000 kg |
| Load cell connection | 4-wire |
| Load cell OIML class | C1 |
| Load cell - Resolution (verifiable) | 1000e |
| Load cell - characteristic value - nominal | 2 mV/V |
| Load cell - characteristic value - variance | 0,002 mV/V |
| Load cell - Y-value | 10000 |
| Load cell - Combined error | 0,05% |
| Load cell - Dead load [Min] (%) | 0% |
| Measuring applications | force mass |
| Load cell - Input resistance - nominal | 800 Ω |
| Load cell - Output resistance - nominal | 700 Ω |
| Load cell - Isolation resistance - [Min] | 5000 MΩ |
| Load cell - Recommended excitation voltage [Min] | 10 V |
| Load cell - Recommended excitation voltage [Max] | 15 V |
| Load cell - Input resistance - variance | 30 Ω |
| Load cell - Output resistance - variance | 5 Ω |

Measuring range force [Max] (N) 50 kN
Directions of force compression

Approval

CE mark ✓

Construction

Design Bending ring
Material stainless steel
Cable length 10 m
Dimension (Ø×H) 82×44 mm

Functions

IP protection - complete device IP68

Environmental conditions

Use temperature [Min] -10 °C
Use temperature [Max] 40 °C
Ambient temperature [Min] -50 °C
Ambient temperature [Max] 70 °C

Packing & Shipping

Readability force [d] (N) 1 d
Dimensions packaging (W×D×H) 250×155×60 mm
Net weight 1,1 kg
Shipping method Parcel service
Net weight approx. 1,2 kg
Gross weight approx. 1,2 kg
Shipping weight 1,151 kg

Services (optional)

Article number for factory calibration (compressive force) 961-265V

Pictograms

STANDARD



OPTION

