

KERN CT 1500-3Q1

KERN

Shear beam made from stainless steel



Construction

| | |
|------------------------------|----------------------------|
| Design | Shear beam measuring cell |
| Dimension (W×D×H) | 130×31,5×31,5 mm |
| Material | stainless steel |
| Cable length | 5 m |
| Mounting - force application | Threaded hole M12 |
| Mounting - force dissipation | 2 × through hole Ø 13,5 mm |

Functions

| | |
|---------------------------------|---------------|
| IP protection - complete device | IP68 IP69K |
|---------------------------------|---------------|

Environmental conditions

| | |
|---------------------------|--------|
| Use temperature [Min] | -10 °C |
| Use temperature [Max] | 40 °C |
| Ambient temperature [Min] | -30 °C |
| Ambient temperature [Max] | 70 °C |

Packing & Shipping

| | |
|------------------------------|----------------|
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 250×155×60 mm |
| Net weight | 1 kg |
| Shipping method | Parcel service |
| Net weight approx. | 1,00 kg |
| Gross weight approx. | 1,2 kg |
| Shipping weight | 1,117 kg |

Services (optional)

| | |
|--|----------|
| Article number for factory calibration (compressive force) | 961-264V |
|--|----------|

Pictograms

STANDARD



OPTION



Category

| | |
|------------------|----------------|
| Brand | Sauter |
| Product category | Measuring cell |
| Product group | Load cell |
| Product family | CT Q1 |

Measuring System

| | |
|--|-------------|
| Weighing capacity [Max] | 1500 kg |
| Load cell connection | 6-wire |
| Load cell OIML class | C3 |
| Load cell - Resolution (verifiable) | 3000 e |
| Load cell - characteristic value - nominal | 2 mV/V |
| Load cell - characteristic value - variance | 0,001 mV/V |
| Load cell - Y-value | 10000 |
| Load cell - Combined error | 0,017% |
| Load cell - Dead load [Min] (%) | 0% |
| Measuring applications | mass |
| Load cell - Input resistance - nominal | 400 Ω |
| Load cell - Output resistance - nominal | 350 Ω |
| Load cell - Isolation resistance - [Min] | 5000 MΩ |
| Load cell - Recommended excitation voltage [Min] | 10 V |
| Load cell - Recommended excitation voltage [Max] | 15 V |
| Load cell - Input resistance - variance | 20 Ω |
| Load cell - Output resistance - variance | 3 Ω |
| Directions of force | compression |

Approval

| | |
|---------|---|
| CE mark | ✓ |
|---------|---|