

Counting Scale KERN CXB · CXB-NM



## Entry level model into professional counting, counting resolution of 30,000 points, verification optional

### Features

- Precise counting: The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- Programmable using numerical key pad:
  - required reference quantity
  - known reference weight
- Three displays for weight display (verifiable), reference weight, total pieces
- Fill-to-target function: Target count or target weight can be programmed. When the target weight is reached there is an audible and visual signal
- 10 memories for reference weights
- Counting results memory: adds up all individual piece counts, result is shown in total weight and total pieces

- Integrated ESD protection, which makes it ideal for weighing small plastic parts
- Energy management: Backlight turns off after 5 sec
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Two balances in one: Changes from counting mode to weighing mode at the touch of a key
- Protective working cover included with delivery

- Rechargeable battery pack integrated, as standard, operating time up to 200 h without backlight, charging time approx. 8 h
- Net weight approx. 4,0 kg
- Permissible ambient temperature -10 °C/40 °C

### Technical data

- Large backlit LCD displays, digit height 18 mm
- Weighing plate dimensions, stainless steel, WxD 300x225 mm
- Overall dimensions WxDxH, 300x330x110 mm

### Accessories

- Protective working cover, scope of delivery 5 items, KERN CXB-A01S05
- Internal rechargeable battery pack, operating time up to 200 h without backlight, charging time approx. 8 h, KERN GAB-A04

Note: Official verification is mandatory for commercial trade

### STANDARD



### OPTION



### FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight (Normal) g/piece	Counting resolution Points	Options		
							Verification	DAkks	Calibr. Certificate
KERN							KERN	KERN	
CXB 3K0.2	3	0,2	-	-	1	30.000	-	-	963-127
CXB 6K0.5	6	0,5	-	-	2	30.000	-	-	963-128
CXB 15K1	15	1	-	-	5	30.000	-	-	963-128
CXB 30K2	30	2	-	-	10	30.000	-	-	963-128
Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.									
CXB 3K1NM	3	1	1	20	1	30.000	965-227	-	963-127
CXB 6K2NM	6	2	2	40	2	30.000	965-228	-	963-128
CXB 15K5NM	15	5	5	100	5	30.000	965-228	-	963-128
CXB 30K10NM	30	10	10	200	10	30.000	965-228	-	963-128

**CAL INT**  
**Internal adjusting**  
 Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)

**CAL EXT**  
**Adjusting program CAL**  
 For quick setting up of the balance's accuracy. External adjusting weight required

**ET**  
**EasyTouch**  
 Suitable for the connection, data transmission and control through PC or tablet

**MEMORY**  
**Memory**  
 Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.

**ALIBI**  
**Alibi memory**  
 Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.

**KUP**  
**KERN Universal Port (KUP)**  
 allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort

**RS 232**  
**RS-232 Data interface**  
 To connect the balance to a printer, PC or network

**RS 485**  
**RS-485 Data interface**  
 To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible

**USB**  
**USB Data interface**  
 To connect the balance to a printer, PC or other peripherals

**BT**  
**Bluetooth\* Data interface**  
 To transfer data from the balance to a printer, PC or other peripherals

**WIFI**  
**WIFI Data interface**  
 To transfer data from the balance to a printer, PC or other peripherals

**SWITCH**  
**Control outputs**  
 (optocoupler, digital I/O)  
 To connect relays, signal lamps, valves, etc.

**ANALOG**  
**Analogue interface**  
 to connect a suitable peripheral device for analogue processing of the measurements

**DUAL**  
**Interface for second balance**  
 For direct connection of a second balance

**LAN**  
**Network interface**  
 For connecting the scale to an Ethernet network

**KCP PROTOCOL**  
**KERN Communication Protocol (KCP)**  
 It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems

**GLP INTERN**  
**GLP/ISO log intern**  
 The balance displays weight, date and time, independent of a printer connection

**GLP PRINTER**  
**GLP/ISO log Printer**  
 With weight, date and time. Only with KERN printers.

**PCS**  
**Piece counting**  
 Reference quantities selectable. Display can be switched from piece to weight

**RECIPE A**  
**Recipe level A**  
 The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out

**RECIPE B**  
**Recipe level B**  
 Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display

**SUM A**  
**Totalising level A**  
 The weights of similar items can be added together and the total can be printed out

**PERCENT**  
**Percentage determination**  
 Determining the deviation in % from the target value (100 %)

**UNIT**  
**Weighing units**  
 Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

**TOL**  
**Weighing with tolerance range (Checkweighing)**  
 Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model

**MOVE**  
**Hold function**  
 (Animal weighing program)  
 When the weighing conditions are unstable, a stable weight is calculated as an average value

**IP**  
**Protection against dust and water splashes IPxx**  
 The type of protection is shown in the pictogram

**UNDER**  
**Suspended weighing**  
 Load support with hook on the underside of the balance

**BATT**  
**Battery operation**  
 Ready for battery operation. The battery type is specified for each device

**ACCU**  
**Rechargeable battery pack**  
 Rechargeable set

**MULTI**  
**Universal plug-in power supply**  
 with universal input and optional input socket adapters for  
 A) EU, CH, GB  
 B) EU, CH, GB, US  
 C) EU, CH, GB, US, AUS

**230 V**  
**Plug-in power supply**  
 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available

**230 V**  
**Integrated power supply unit**  
 Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request

**DMS**  
**Weighing principle Strain gauges**  
 Electrical resistor on an elastic deforming body

**T-FORK**  
**Weighing principle Tuning fork**  
 A resonating body is electromagnetically excited, causing it to oscillate

**FORCE**  
**Weighing principle Electromagnetic force compensation**  
 Coil inside a permanent magnet. For the most accurate weighings

**SC TECH**  
**Weighing principle Single cell technology**  
 Advanced version of the force compensation principle with the highest level of precision

**M +3 DAYS**  
**Conformity Assessment**  
 The time required for conformity assessment is specified in the pictogram

**DAkkS +3 DAYS**  
**DAkkS calibration possible (DKD)**  
 The time required for DAkkS calibration is shown in days in the pictogram

**ISO +4 DAYS**  
**Factory calibration (ISO)**  
 The time required for Factory calibration is shown in days in the pictogram

**1 DAY**  
**Package shipment**  
 The time required for internal shipping preparations is shown in days in the pictogram

**2 DAYS**  
**Pallet shipment**  
 The time required for internal shipping preparations is shown in days in the pictogram

\* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.