KERN EMB 500-1BE



Entry level laboratory balance with tremendous weighing performance



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EMB
Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	500 g
Readability [d]	0,1 g
Resolution	5.000
Linearity	± 0,2 g
Reproducibility	0,1 g
Tare range	500 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	500 g (M1)
Possible calibration points	500 g
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,5 g
Maximum creep (15 minutes)	400 mg
Maximum creep (30 minutes)	800 mg

1

Approval

CE mark

Display	
Display type	LCD
Display screen size	58×18 mm
Display backlight	no
Display digit height	15 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	170×244×39 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Dimensions weighing surface (Ø)	150 mm
Functions	
Number of keys for operation	2
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Underfloor weighing	Hook (included in delivery)
IP protection - complete device	-
Power Supply	
Power Supply Input voltage device / power [Max]	9 V, 300 mA
	9 V, 300 mA Power adapter
Input voltage device / power [Max]	
Input voltage device / power [Max] Plug-in power supply type Supplied power supply	Power adapter Battery EURO
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	Power adapter Battery EURO UK
Input voltage device / power [Max] Plug-in power supply type Supplied power supply	Power adapter Battery EURO UK US
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional	Power adapter Battery EURO UK US CH
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional	Power adapter Battery EURO UK US CH Rchrg. battery optional
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional	Power adapter Battery EURO UK US CH
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating	Power adapter Battery EURO UK US CH Rchrg. battery optional
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese)
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery voltage	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery voltage Battery operating time	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery voltage Battery operating time Environmental conditions	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V 35 h
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery voltage Battery operating time Environmental conditions Humity of environment [Max]	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V 35 h 35 h

Storage temperature [Min]

-20 °C

KERN EMB 500-1BE



Entry level laboratory balance with tremendous weighing performance

Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	205×266×75 mm
Net weight	0,52 kg
Shipping method	Parcel service
Net weight approx.	0,55 kg
Gross weight approx.	0,70 kg
Shipping weight	0,8 kg
Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

