

KERN EMS 300-3

KERN

Entry level model in the low-cost range with large weighing plate



Display

Display type	LCD
Display backlight	no
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	200×280×65 mm
Dimensions rectangular draught shield - inner (W×D×H)	145×145×65 mm
Dimensions rectangular draught shield - outer (W×D×H)	165×165×80 mm
Dimensions completely mounted (W×D×H)	200×280×126 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic, with conductive lacquer
Dimensions weighing surface (Ø)	105 mm

Functions

Number of keys for operation	5
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓
Recipe/summing level	Rez A (Net total)
IP protection - complete device	-

Counting

Smallest piece weight when piece counting - laboratory conditions	2 mg
Smallest piece weight when piece counting - normal conditions	20 mg
Reference quantity	5, 10, 20, 25, 50
Counting resolution (laboratory conditions)	150.000

Power Supply

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	9 V, 300 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK

Category

Brand	KERN
Product category	Laboratory balance
Product group	School balance
Product family	EMS

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	300 g
Readability [d]	0,001 g
Resolution	300.000
Linearity	± 0,005 g
Reproducibility	0,002 g
Tare range	300 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	300 g (F1)
Possible calibration points	300 g
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,005 g
Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg

Approval

CE mark	✓
---------	---

KERN EMS 300-3

Entry level model in the low-cost range with large weighing plate

	US CH
Rechargeable battery optional	Rchrg. battery optional
Rechargeable battery operating time - backlight off	50 h
Battery	9 V block
Battery / accumulator type	Alkali(-Manganese)
Battery connection	9V Bloc
Battery operating time	40 h

Environmental conditions

Humidity of environment [Min]	40 %
Humidity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	240×485×170 mm
Net weight	1,4 kg
Shipping method	Parcel service
Net weight approx.	1,4 kg
Gross weight approx.	2,2 kg
Shipping weight	4 kg

Services (optional)

Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

