## KERN FL 5K



Powerful digital force gauge with graphic assisted display for tensile and compressive force measurements with external load cell



Category	
	•
Brand	Sauter
Product categoriy	Force measurement
Product group	Digital force gauges (external measuring cell)
Product family	FL-M
Measuring System	
Default unit	Ν
Tolerance (% of [Max])	0,2%
Measuring range force [Max] (N)	5 kN
Readability force [d] (N)	2 N
Directions of force	tension compression
Measuring head measuring frequency	1000 Hz
Number of platforms / channels	1
Overload protection (% of [Max])	120%
Internal data memory: Number of value groups	1
Internal data memory: Number of individual values	500

## Approval

CE mark

DisplayDisplay typeLCDDisplay digit height8,5 mmScreen reversible✓

1

## Construction

Dimension display device (W×D×H)	175×75×30 mm
Dimension housing (W×D×H)	175×75×30 mm

Dimensional approximately measurated	
Dimensions completely mounted (W×D×H)	175×75×30 mm
Material display housing	Aluminium
Material housing	metal, lacquered
Load support (tensile force)	Rod end
Mounting - force application	Threaded hole M12
Mounting - force dissipation	Threaded hole M12
Dimensions load cell	69,2×59,5×23,7 mm
Functions	
Analogue signal	✓
Limit-setting function	✓
Memory function	1
	RS-232 standard
Interfaces	USB-Device
	Analog (0 +/-2V)
Power Supply	
Input voltage power supply /	100 V - 240 V
power [Max]	100 v - 240 v
Input voltage device / power [Max]	9 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Accu & Power supply
Plug-in power supply / adapter for	EURO
countries - included with the	СН
delivery	FUDO
	EURO AUS
Plug-in power supply / adapter for	AU3
i lug ili power supply / adapter ioi	l IK
countries - optional	UK US
countries - optional	US CH
	US
countries - optional Rechargeable battery charging time Rechargeable battery operating	US CH 8 h
countries - optional Rechargeable battery charging time	US CH
countries - optional Rechargeable battery charging time Rechargeable battery operating	US CH 8 h
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating	US CH 8 h 8 h
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off	US CH 8 h 8 h 10 h
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type	US CH 8 h 8 h 10 h NiMH
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage	US CH 8 h 8 h 10 h NiMH 750 mAh
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions Ambient temperature [Min]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions Ambient temperature [Min] Ambient temperature [Max]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Min]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V 15 °C 35 °C -10 °C
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions Ambient temperature [Min] Ambient temperature [Max]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V
countries - optional Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage Environmental conditions Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Min]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V 15 °C 35 °C -10 °C
countries - optional  Rechargeable battery charging time Rechargeable battery operating time - backlight on Rechargeable battery operating time - backlight off Battery / accumulator type Battery capacity Battery voltage  Environmental conditions Ambient temperature [Min] Ambient temperature [Max] Storage temperature [Max]	US CH 8 h 8 h 10 h NiMH 750 mAh 4,8 V 15 °C 35 °C -10 °C

## KERN FL 5K



Powerful digital force gauge with graphic assisted display for tensile and compressive force measurements with external load cell

Dimensions packaging (W×D×H)	370×325×115 mm
Net weight	1,305 kg
Shipping method	Parcel service
Net weight approx.	1,4 kg
Gross weight approx.	2,4 kg
Shipping weight	2,8 kg
Services (optional)	
Article number for DAkkS calibration (tensile force)	963-163
Article number for DAkkS calibration (compressive force)	963-263
Article number for DAkkS calibration (tensile force/ compressive force)	963-363
Article number for factory calibration (tensile force)	961-163
Article number for factory calibration (compressive force)	961-263
Article number for factory calibration (tensile force/ compressive force)	961-363

Pictograms

STANDARD



OPTION

