

KERN FOB 5K-3NS

KERN

Compact stainless steel balance with protection type IP65 against dust and water splashes



Approval

CE mark ✓

Display

Display type LCD
Display backlight no
Display digit height 20 mm

Construction

Dimension housing (W×D×H) 150×170×40 mm
Dimensions weighing platform (W×D×H) 150×120×8 mm
Material housing stainless steel
Material weighing plate stainless steel
Material platform Stainless steel
Dimensions weighing surface (W×D) 120×150 mm

Functions

Number of keys for operation 3
3 min
off
Auto-off interval(s) in battery mode/rechargeable battery mode 4 min
5 min
2 min
Tare function manual (multi)
Underfloor weighing None
IP protection - complete device IP65

Power Supply

Input voltage power supply / power [Max] 230 V AC, 50 Hz
Input voltage device / power [Max] 9 V, 100 mA
Plug-in power supply type Power adapter
Supplied power supply Battery
Plug-in power supply / adapter for countries - optional EURO
UK
CH
Battery 9 V block
Battery / accumulator type Alkali(-Manganese)
Battery connection 9V Bloc
Battery capacity 560 mAh
Battery voltage 9 V
Battery operating time 20 h
Battery operating time - backlight off 20 h

Category

Brand KERN
Product category Industrial scale
Product group Stainless steel bench scale
Product family FOB-NS

Measuring System

Construction type of the scale Single-range balance
Number of weighing ranges 1
Weighing system Strain gauge
Weighing capacity [Max] 5000 g
Readability [d] 1 g
Resolution 5.000
Linearity ± 2 g
Reproducibility 1 g
Tare range 5000 g
Default unit g
Units g
dwt
ozt
lb
oz
Adjustment options Adjusting with external weight
Recommended adjusting weight 5 kg (M1)
Possible calibration points 5 kg
Stabilization time 2 s
Warm-up time 10 min
Eccentric loading at 1/3 [Max] 3 g
Maximum creep (15 minutes) 4 g
Maximum creep (30 minutes) 8 g

KERN FOB 5K-3NS

Compact stainless steel balance with protection type IP65 against dust and water splashes

Environmental conditions

Humidity of environment [Min]	25 %
Humidity of environment [Max]	95 %
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	255×195×75 mm
Net weight	0,76 kg
Shipping method	Parcel service
Net weight approx.	0,80 kg
Gross weight approx.	0,90 kg
Shipping weight	0,878 kg

Services (optional)

Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

