KERN FS 2-10KSP1



Ready-assembled set consisting of premium force gauge FS 2 and external "S" measuring cell CS 1000-3P1 for tensile and compressive force measurements



Category	
Brand	Sauter
Product categoriy	Force measurement
Product group	Force measuring device set
Product family	FS SP1

Measuring System	
Default unit	N
Measuring range force [Max] (N)	10 kN
Readability force [d] (N)	2 N
Directions of force	tension compression
Measuring head measuring frequency	1000 Hz
Number of platforms / channels	2

Approval		
CE mark	✓	

Display	
Display type	TFT, color
Display resolution	320×480
Languages of the user interface	German English French Spanish Italian

Construction		
Material display housing	Plastics	
Material housing	plastic	

Mounting - force application	Threaded hole M12
Mounting - force dissipation	Threaded hole M12
Dimensions load cell	50,8×76,2×25,4 mm

Functions	
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Peak function	✓
Statistic function	✓
Memory function	✓
Interfaces	USB-Device

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A
Plug-in power supply type	USB including power supply
Supplied power supply	Accu & Power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	UK
Rechargeable battery charging time	8 h
Rechargeable battery operating time - backlight on	5 h
Rechargeable battery operating time - backlight off	8 h
Battery / accumulator type	Li-lon
Battery connection	2-pole tub connector
Battery capacity	2.400 mAh
Battery voltage	3,7 V

Packing & Shipping	
Readability force [d] (N)	3 d
Net weight	0,958 kg
Shipping method	Parcel service
Net weight approx.	1,00 kg
Gross weight approx.	2,0 kg
Shipping weight	1,91 kg
Services (optional)	
Article number for factory	961-164

961-264

calibration (tensile force)
Article number for factory

calibration (compressive force)

1

KERN FS 2-10KSP1



Ready-assembled set consisting of premium force gauge FS 2 and external "S" measuring cell CS 1000-3P1 for tensile and compressive force measurements

Article number for factory calibration (tensile force/compressive force)

961-364

Pictograms

STANDARD



OPTION

ACCU



230 V

3 DAYS