KERN FS 2-5KRY1



Ready-assembled set consisting of premium force gauge FS 2 and load cell CR 500-1Y1 for tensile and compressive force measurements



Category	
Brand	Sauter
Product categoriy	Force measurement
Product group	Force measuring device set
Product family	FS RY1

Measuring System	
Default unit	N
Measuring range force [Max] (N)	5 kN
Readability force [d] (N)	1 N
Directions of force	tension compression
Measuring head measuring frequency	1000 Hz
Number of platforms / channels	2

Approval		
CE mark	✓	

Display	
Display type	TFT, color
Display resolution	320×480
Languages of the user interface	German English French Spanish Italian

Construction	
Material display housing	Plastics
Material housing	plastic

Mounting - force application	Threaded hole M16 × 1,5
Mounting - force dissipation	8 × through hole Ø 6,5 mm
Dimensions load cell (cylindrical)	105×37 mm

Functions	
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Peak function	✓
Statistic function	✓
Memory function	✓
Interfaces	USB-Device

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A
Plug-in power supply type	USB including power supply
Supplied power supply	Accu & Power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	UK
Rechargeable battery charging time	8 h
Rechargeable battery operating time - backlight on	5 h
Rechargeable battery operating time - backlight off	8 h
Battery / accumulator type	Li-lon
Battery connection	2-pole tub connector
Battery capacity	2.400 mAh
Battery voltage	3,7 V

Packing & Shipping	
Readability force [d] (N)	3 d
Net weight	2 kg
Shipping method	Parcel service
Net weight approx.	2,0 kg
Gross weight approx.	3,0 kg
Shipping weight	2,985 kg
Services (optional)	
Article number for DAkkS calibration (tensile force)	963-161

963-263

Article number for DAkkS

calibration (compressive force)

1

KERN FS 2-5KRY1



Ready-assembled set consisting of premium force gauge FS 2 and load cell CR 500-1Y1 for tensile and compressive force measurements

Article number for DAkkS calibration (tensile force/compressive force)

963-363

Pictograms

STANDARD



OPTION

ACCU



230 V

3 DAYS