## KERN HCN 200K500IP



Robust, compact hanging scale with high level of protection against dust and water spray



## Category

Brand	KERN
Product categoriy	Industrial scale
Product group	Hanging scale
Product family	HCN

## Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	200 kg
Readability [d]	0,5 kg
Resolution	400
Linearity	± 1 kg
Reproducibility	0,5 kg
Default unit	kg
Units	kg Ib N
Adjustment options	Adjusting with external weight
Recommended adjusting weight	100 kg (M3)
Stabilization time	2 s
Warm-up time	10 min
Eccentric/Off-centre loading is not possible	1
Maximum creep (15 minutes)	1 kg
Maximum creep (30 minutes)	2 kg
Tolerance (% of [Max])	0,5%
Internal measuring frequency	5 Hz

1

Approval

CE mark

Display	
Display type	LCD
Display digit height	12 mm
Construction	
Dimension housing (W×D×H)	96×48×179 mm
Material housing	stainless steel
Material load hook	stainless steel
Material load cell(s)	Stainless steels
Functions	
Number of keys for operation	3
Auto-off interval(s) in mains power mode	3 min
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Hold function	1
Underfloor weighing	None
IP protection - complete device	IP65
Power Supply	
Supplied power supply	Battery
Battery	2×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery voltage	3 V
Battery operating time	200 h
Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Max]	60 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	150×220×73 mm
Net weight	0,5 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	1,2 kg
Shipping weight	1,1 kg
Services (optional)	
Article number for adjustment at	961-249
the location of installation	, VI 2T/

## KERN HCN 200K500IP



Robust, compact hanging scale with high level of protection against dust and water spray

Article number for DAkkS<br/>calibration963-129HArticle number for certificate of<br/>conformity (verification)969-517

Pictograms

STANDARD



**OPTION** 

DAkks +3 days