# KERN **KXP 150V20M**

**KERN**

Platform: weighing plate of stainless steel, painted steel base, silicone-coated aluminium load cell with protection against dust and water splashes IP65



| IP protection - load cell | IP65 |
|---|---|

## Packing & Shipping

| | |
|---|---|
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 600×500×240 mm |
| Net weight | 17,5 kg |
| Shipping method | Parcel service |
| Net weight approx. | 18 kg |
| Gross weight approx. | 20 kg |
| Shipping weight | 20 kg |

## Category

| | |
|---|---|
| Brand | KERN |
| Product categoriy | Component |
| Product group | Platform |
| Product family | KXP-V20-IP65 |

## Services (optional)

| | |
|---|---|
| Article number for conformity assessment | 965-229 |
| Article number for DAkkS calibration | 963-129 |

## Measuring System

| | |
|---|---|
| Weighing capacity [Max] | 60 kg; 150 kg |
| Readability [d] | 5 g |
| Minimum weight [Min] | 400 g; 1 kg |
| Loadcell type | aluminium IP65 silicone-coated |
| Load cell connection | 6-wire |

## Pictograms

**STANDARD**



**FACTORY**



## Approval

| | |
|---|---|
| Verification scale interval [e] | 20 g; 50 g |
| Conformity assessment possible ex works | ✓ |

## Construction

| | |
|---|---|
| Dimensions weighing platform (W×D×H) | 500×400×125 mm |
| Material weighing plate | stainless steel |
| Material platform | steel, varnished |
| Dimensions weighing surface (W×D) | 500×400 mm |
| Cable length | 3 m |
| Allowed cable length display device [Max] | 10 m |
| Transport safety lock - bolt torque | 0,1 Nm |
| Material load cell(s) | aluminium |
| Load cells - number | 1 |
| Levelling feet adjustable | ✓ |

## Functions

| | |
|---|---|
| IP protection - complete device | IP65 (load cell) |