KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional



\cap	to	σO	n
Са	ιe	gυ	'i y

Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPE

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Resolution	2.500
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	-249,9 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg

Zulassung

CE mark	1	
Accuracy classe	III	
Verification scale interval [e]	0,1 kg	

Conformity assessment possible ex works	\checkmark
Approved as a medical device	1
Display	
Display type	LCD
Display backlight	✓
Display digit height - smallest digit	2 mm
Display digit height	25 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	200×55×128 mm
Dimensions weighing platform (W×D×H)	365×360×80 mm
Dimensions completely mounted (W×D×H)	365×570×1030 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	plastic
Dimensions weighing surface (W×D)	327×333 mm
Level indicator	1
Transport wheels	1
Stand height	940 mm
Stand height Functions	940 mm
-	940 mm 7
Functions	
Functions Number of keys for operation Auto-off interval(s) in mains power	7 5 min 30 min selectable
Functions Number of keys for operation Auto-off interval(s) in mains power mode	7 5 min 30 min selectable 15 min 3 min 5 min 30 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode PreTare function	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare function Tare function	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ↓ ✓ manual (single & multi)
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare function Tare function Hold functionFunction for averaging under	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ✓ manual (single & multi) ✓
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare functionTare functionHold functionFunction for averaging under unstable weighing conditions	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ✓ manual (single & multi) ✓
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare functionTare functionHold functionFunction for averaging under unstable weighing conditionsFunction for BMI calculation	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ✓ manual (single & multi) ✓
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare functionTare functionHold functionFunction for averaging under unstable weighing conditionsFunction for BMI calculationInterfaces	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ✓ manual (single & multi) ✓
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode PreTare function PreTare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply /	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ↓ manual (single & multi) ↓ RS-232 standard 100 V - 240 V, 50 / 60
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modePreTare functionTare functionHold functionFunction for averaging under unstable weighing conditionsFunction for BMI calculation InterfacesPower SupplyInput voltage power supply / power [Max]	7 5 min 30 min selectable 15 min 3 min 5 min 30 min 15 min ✓ manual (single & multi) ✓ Manual (single & multi) ✓ manual (single & multi) ✓ 100 V - 240 V, 50 / 60 Hz

KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional

Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions	
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	0° 00

Packing & Shipping

1 d
1010×290×445 mm
11,26 kg
Parcel service
12 kg
14 kg
26,1 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

