## KERN MWS 300K-1LM



Symbol language

Stretcher scale with low overall height for easy access – with approval for medical use and optionally with verification



Category	
Brand	KERN
Product categoriy	Medical scale
Product group	Stretcher Scale
Product family	MWS-L

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	300 kg
Readability [d]	0,1 kg
Resolution	3.000
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Default unit	kg
Units	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	300 kg (M1)
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg

Approval	
CE mark	✓
Accuracy classe	III
Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	✓
Approved as a medical device	✓

Display	
Display type	LCD
Display digit height	25 mm

Construction	
Constituction	
Dimension display device (W×D×H)	210×110×50 mm
Dimension housing (W×D×H)	1500×860×68 mm
Dimensions weighing platform (W×D×H)	1500×860×68 mm
Dimensions completely mounted (W×D×H)	1500×860×68 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	steel, lacquered
Dimensions weighing surface (W×D)	800×1200 mm
Cable length	1,8 m
Display device cable length	2 m
Levelling feet adjustable	✓
Wall mount	✓
Transport wheels	✓

Languages of the user interface

Functions	
Number of keys for operation	20
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off 4 min 5 min 2 min
PreTare function	✓
Tare function	manual (multi)
Hold function	✓
Function for averaging under unstable weighing conditions	✓
Function for BMI calculation	✓
Interfaces	RS-232 standard

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK

1

## KERN MWS 300K-1LM



Stretcher scale with low overall height for easy access – with approval for medical use and optionally with verification

	US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	14 h
Rechargeable battery operating time - backlight off	45 h
Battery	6×1.5 V AA
Battery / accumulator type	NiMH
Battery operating time	50 h

Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	1650×1008×123 mm
Net weight	42 kg
Shipping method	Freight
Net weight approx.	42 kg
Gross weight approx.	55 kg
Shipping weight	55 kg

Services (optional)	
Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

## Pictograms STANDARD RS 232 MOVE BATT MULTI 2 DAYS OPTION DAKKS ACCU +3 DAYS



