

KERN OBE 134T241

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories



| | |
|-------------------------------|-----------------|
| Light distribution | 20:80 |
| Interpupillary distance [Max] | 75 mm |
| Interpupillary distance [Min] | 50 mm |
| Colour temperature | 6000 K |
| Cameratype | Tablet camera |
| Camera - Sensor type | Sony CMOS |
| Camera - Sensor size | 1/2,8" |
| Camera - Resolution | 5 MP |
| Camera - Colour depth | Colour |
| Camera - Framerate | 30 fps |
| Camera- Mounting types | C-mount thread |
| Camera - Exposure method | Rolling Shutter |

| Ocular | |
|-----------------------|----------------|
| Ocular field width | HWF |
| Eye point | High Eye Point |
| Ocular magnifications | 10 x |
| Ocular visual field | 18 mm |
| Ocular diameter | 23,2 mm |

| Focussing | |
|---------------------|-------------------------------|
| Fine drive minimum | 0,002 mm |
| Torque regulation | ✓ |
| Field of view [Min] | 0,18 mm |
| Field of view [Max] | 4,5 mm |
| Focusing mechanism | coaxial coarse and fine drive |

| Illumination | |
|--|-------------------|
| Illumination type incident light | none |
| Illumination intensity transmitted light | 3 W |
| Illumination type transmitted light | LED |
| Illuminance | Transmitted light |
| Illumination dimmable | Transmitted light |
| Filter possible | ✓ |

| Functions | |
|------------------------------|---|
| Memory - total size | 128 GB |
| Interfaces | WiFi standard USB 2.0 HDMI MicroSD card slot |
| Supported operating systems | Android |
| Camera - Applicable software | integrated |

| Category | |
|------------------|------------------------|
| Brand | Optics |
| Product category | Microscope |
| Product group | Digital microscope set |
| Product family | OBE-S |

| Approval | |
|----------|---|
| CE mark | ✓ |

| Display | |
|--------------------|-----------|
| Display resolution | 2048×1536 |

| Construction | |
|------------------------------|---|
| Dimension (W×D×H) | 360×235×540 mm |
| Optical system | Finite |
| Tube type | Siedentopf |
| Tube type | Trinocular |
| Tube angle of inclination | 30° |
| Tube 360° rotation | ✓ |
| Lens quality | achromatic |
| | 4× |
| | 10× |
| Standard objectives | 40× |
| | 100× |
| Nosepiece screw-in locations | 4 |
| Eyepieces fixed | ✓ |
| Diopter adjustment | one-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |
| Contrasting methods | Bright field Darkfield (optional) Polarisation (optional) |

KERN OBE 134T241



Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Power Supply

| | |
|---|-------------------|
| Input voltage power supply / power [Max] | 100 - 240 V |
| Input voltage device / power [Max] | 5 V, 1 A |
| Plug-in power supply type | Power adapter |
| Supplied power supply | Power supply unit |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| | AUS |
| Plug-in power supply / adapter for countries - optional | UK |
| | US |
| | CH |

Environmental conditions

| | |
|---------------------------|-------|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |

Packing & Shipping

| | |
|------------------------------|----------------|
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 560×440×330 mm |
| Net weight | 5,978 kg |
| Shipping method | Parcel service |
| Net weight approx. | 6 kg |
| Gross weight approx. | 8 kg |
| Shipping weight | 16,3 kg |

Pictograms

STANDARD



OPTION

