

KERN ORM 1AL

Digital measurement of refraction index for universal application

KERN



Category

Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORM-AL

Measuring System

Automatic temperature compensation (ATC)	✓
Measuring method	Total reflection
Area of application	Alcohol
Percentage by volume	0-80%(v/v) @ 1%(v/v) ± 1%(v/v)
Appropriate calibration liquid	0 % (distilled water)
Measurement temperature [Min] (°C)	0 °C
Measurement temperature [Max] (°C)	40 °C
Brix scale	✓
Readout Brix	0,1 %
Measuring range Brix [Min]	0 %
Measuring range Brix [Max]	50 %
Accuracy Brix	±0,2 %
Scale for Refractive index	✓
Readout refractive index	0,0001 nD
Measuring range refractive index [Min]	1,3330 nD
Measuring range refractive index [Max]	1,4200 nD
Accuracy refractive index	±0,0003 nD
Scale percent by mass	✓
Readout percent by mass	1 %
Measuring range percent by mass [Min]	0 %

Measuring range percent by mass [Max]	72 %
Accuracy percent by mass	± 1 %
Scale volume percentage	✓
Readout volume percentage	1 %
Measuring range volume percentage [Min]	0 %
Measuring range volume percentage [Max]	80 %
Accuracy volume percentage	± 1 %

Zulassung

CE mark	✓
---------	---

Construction

Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Material prism	ZLaF3 lanthanum flint glass nd=1.85544
Prism lid	✓

Functions

Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec
IP protection - complete device	IP65
Averaging measurement	✓
Averaging measurement amount	15

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali-(Manganese)
Battery connection	Pad + Spring
Battery capacity	1.300 mAh
Battery voltage	1,5 V

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	170×110×50 mm
Net weight	0,14 kg
Shipping method	Parcel service

KERN ORM 1AL



Digital measurement of refraction index for universal application

Net weight approx. 0,15 kg

Gross weight approx. 0,35 kg

Shipping weight 0,31 kg

Services (optional)

Article number for factory calibration 961-290

Pictograms

STANDARD

