KERN OSF 439



The practical and robust product for schools, training centres, the workshop and laboratory



| Category | |
|-------------------|-------------------|
| Brand | Optics |
| Product categoriy | Microscope |
| Product group | Stereo microscope |
| Product family | OSF-43 |

| Approval | | |
|----------|---|--|
| CE mark | ✓ | |

| Construction | |
|-------------------------------|----------------|
| Dimension (W×D×H) | 230×180×275 mm |
| Optical system | Greenough |
| Tube type | Binocular |
| Tube angle of inclination | 45° |
| | 4× |
| Standard objectives | 1× |
| | 2× |
| Eyepieces fixed | ✓ |
| Diopter adjustment | one-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |
| Contrasting methods | Bright field |
| Interpupillary distance [Max] | 75 mm |
| Interpupillary distance [Min] | 55 mm |

| Ocular | |
|-----------------------|---------|
| Ocular field width | WF |
| Ocular magnifications | 10 x |
| Ocular visual field | 20 mm |
| Ocular diameter | 30,5 mm |

| Focussing | |
|---------------------|--------------|
| Torque regulation | ✓ |
| Working distance | 57 mm |
| Field of view [Min] | 5 mm |
| Field of view [Max] | 20 mm |
| Focusing mechanism | coarse drive |

| Illumination | |
|--|--------------------------------------|
| Illumination type incident light | LED |
| Illumination intensity incident light | 1 W |
| Illumination intensity transmitted light | 0,35 W |
| Illumination type transmitted light | LED |
| Illuminance | Reflected light Transmitted light |

| Power Supply | |
|---|-----------------------|
| Input voltage power supply / power [Max] | 100 - 240 V |
| Input voltage device / power [Max] | 4,5 V |
| Plug-in power supply type | Power adapter |
| Supplied power supply | Power supply unit |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| Plug-in power supply / adapter for countries - optional | AUS UK US CH |

| Environmental conditions | | |
|---------------------------|-------|--|
| Storage temperature [Min] | -5 °C | |
| Storage temperature [Max] | 40 °C | |

| 1 d |
|----------------|
| 340×310×225 mm |
| 2,323 kg |
| Parcel service |
| 2,4 kg |
| 2,8 kg |
| 4,7 kg |
| |

1

KERN OSF 439



The practical and robust product for schools, training centres, the workshop and laboratory

Pictograms

STANDARD

