KERN OZL 961



Predefined stereo microscope set with simple telescopic arm and 4.5 W ring illumination unit for greater flexibility at the workstation



| Category | |
|-------------------|-----------------------|
| Brand | Optics |
| Product categoriy | Microscope |
| Product group | Stereo microscope set |
| Product family | OZL-9 |

| Approval | | |
|----------|---|--|
| CE mark | ✓ | |

| Construction | |
|-------------------------------|----------------|
| Dimension (W×D×H) | 700×255×600 mm |
| Optical system | Greenough |
| Tube type | Binocular |
| Tube angle of inclination | 45° |
| Tube 360° rotation | ✓ |
| Diopter adjustment | both-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |
| Contrasting methods | Bright field |
| Interpupillary distance [Max] | 75 mm |
| Interpupillary distance [Min] | 55 mm |

| Ocular | |
|-----------------------|----------------|
| Ocular field width | HWF |
| Eye point | High Eye Point |
| Ocular magnifications | 10 x |
| Ocular visual field | 20 mm |
| Ocular diameter | 30 mm |

| Focussing | |
|-------------------|---|
| Torque regulation | ✓ |

| Working distance | 100 mm |
|------------------------------------|--------------|
| Zoom [Min] | 0,7 x |
| Zoom [Max] | 4,5 x |
| Magnification ratio | 6,4:1 |
| Field of view [Min] | 4,4 mm |
| Field of view [Max] | 28,6 mm |
| Focusing mechanism | coarse drive |
| Sample height [Max] | 140 mm |
| Standard total magnification [Min] | 7 x |
| Standard total magnification [Max] | 45 x |

| Illumination | |
|---------------------------------------|-----------------|
| Illumination type incident light | LED |
| Illumination intensity incident light | 4,5 W |
| Illuminance | Reflected light |
| Illumination dimmable | Incident light |

| Power Supply | |
|---------------------------------------------------------|-------------------------------|
| Input voltage power supply / power [Max] | 100 - 240 V |
| Input voltage device / power [Max] | 100 - 240 V |
| Plug-in power supply type | Built-in power supply |
| Plug-in power supply / adapter for countries - optional | EURO AUS UK US CH |

| Environmental conditions | |
|---------------------------|-------|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |

| Packing & Shipping | |
|------------------------------|----------------|
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 820×420×240 mm |
| Net weight | 17 kg |
| Shipping method | Parcel service |
| Net weight approx. | 17 kg |
| Gross weight approx. | 20 kg |
| Shipping weight | 19,5 kg |

Pictograms

1