KERN OZM 933UK



Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace



Category

Brand	Optics
Product categoriy	Microscope
Product group	Stereo microscope set
Product family	OZM-9

Construction

Optical system	Greenough
Tube type	Trinocular
Tube angle of inclination	45°
Tube 360° rotation	✓
Diopter adjustment	both-sided
Diopter adjustment [Min]	-6
Diopter adjustment [Max]	6
Contrasting methods	Bright field
Light distribution	100:0
Interpupillary distance [Max]	76 mm
Interpupillary distance [Min]	52 mm

Ocular

Ocular field width	HSWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	23 mm
Ocular diameter	30 mm

Focussing

\checkmark
110 mm
0,7 x
4,5 x
6,4:1

Field of view [Min]	5,1 mm
Field of view [Max]	32,8 mm
Focusing mechanism	coarse drive
Sample height [Max]	130 mm
Standard total magnification [Min]	7 x
Standard total magnification [Max]	45 x
Illumination	
Illumination type incident light	LED
Illumination intensity incident light	4,5 W
Illuminance	Reflected light
Illumination dimmable	Incident light
Power Supply	
Input voltage power supply /	100 - 240 V
power [Max]	100 040 1/
Input voltage device / power [Max]	100 - 240 V
Plug-in power supply type	Built-in power supply
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the	UK
delivery	OK
-	
Environmental conditions	
Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C
Packing & Shipping	
Packing & Shipping Readability force [d] (N)	1 d
	1 d 700×520×350 mm
Readability force [d] (N)	
Readability force [d] (N) Dimensions packaging (W×D×H)	700×520×350 mm
Readability force [d] (N) Dimensions packaging (W×D×H) Net weight	700×520×350 mm 28 kg
Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method	700×520×350 mm 28 kg Parcel service

Pictograms