## KERN OZP 558



Professional and powerful – thanks to its extremely large magnification range, strong illumination and firstclass optics



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Stereo microscope
Product family	OZP-5
Approval	
CE mark	1
Construction	
Dimension (W×D×H)	330×285×470 mm
Optical system	Greenough
Tube type	Trinocular
Tube angle of inclination	35°
Tube 360° rotation	1
Diopter adjustment	both-sided
Diopter adjustment [Min]	-6
Diopter adjustment [Max]	6
Contrasting methods	Bright field Darkfield (optional)
Light distribution	100:0
Interpupillary distance [Max]	76 mm
Interpupillary distance [Min]	52 mm

Ocular	
Ocular field width	HSWF
Ocular magnifications	10 x
Ocular visual field	23 mm
Ocular diameter	30 mm

1

## Focussing

Torque regulation

Working distance	108 mm
Zoom [Min]	0,6 x
Zoom [Max]	5,5 x
Magnification ratio	9,2:1
Field of view [Min]	4,2 mm
Field of view [Max]	38,3 mm
Focusing mechanism	coarse drive
Sample height [Max]	110 mm
Standard total magnification [Min]	6 x
Standard total magnification [Max]	55 x
Illumination	
Illumination type incident light	LED
Illumination intensity incident light	3 W
Illumination intensity transmitted light	3 W
Illumination type transmitted light	LED
	Reflected light
Illuminance	Transmitted light
	Incident light +
Illumination dimmable	Transmitted light,
	separate
Power Supply	
Input voltage power supply / power [Max]	110 - 220 V
	110 - 220 V 110 - 220 V
power [Max]	
power [Max] Input voltage device / power [Max]	110 - 220 V
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	110 - 220 V Built-in power supply Power supply unit
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the	110 - 220 V Built-in power supply
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	110 - 220 V Built-in power supply Power supply unit EURO
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	110 - 220 V Built-in power supply Power supply unit EURO AUS
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	110 - 220 V Built-in power supply Power supply unit EURO AUS UK
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	110 - 220 V Built-in power supply Power supply unit EURO AUS
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min]	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max]	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N)	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H)	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d 385×370×330 mm
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d 385×370×330 mm 4,6816 kg
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight Shipping method	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d 385×370×330 mm 4,6816 kg Parcel service
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H) Net weight	110 - 220 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d 385×370×330 mm 4,6816 kg

## KERN OZP 558



Professional and powerful – thanks to its extremely large magnification range, strong illumination and firstclass optics

Shipping weight 9,4 kg

Pictograms

STANDARD



OPTION

