

# KERN TC 1250-0.1FN

**KERN**

Robust coating thickness gauge – compact and easy to use



Display digit height 10 mm

## Construction

Dimension (W×D×H)	131×65×28 mm
Dimension housing (W×D×H)	131×65×28 mm
Dimensions completely mounted (W×D×H)	131×65×28 mm
Material housing	plastic

## Functions

Increase in measurement accuracy possible ✓

## Power Supply

Supplied power supply	Battery
Battery	4×1.5 V AAA
Battery / accumulator type	Alkali(-Manganese)
Battery capacity	1.100 mAh
Battery voltage	1,5 V
Battery operating time	50 h

## Environmental conditions

Ambient temperature [Min]	0 °C
Ambient temperature [Max]	50 °C
Storage temperature [Min]	0 °C
Storage temperature [Max]	50 °C

## Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	260×215×75 mm
Net weight	0,08 kg
Shipping method	Parcel service
Net weight approx.	0,10 kg
Gross weight approx.	0,75 kg
Shipping weight	0,8 kg

## Services (optional)

Article number for factory calibration	961-112
----------------------------------------	---------

## Category

Brand	Sauter
Product category	Coating thickness measuring device
Product group	Digital coating thickness gauge
Product family	TC

## Measuring System

Units	µm inch (mil)
Tolerance (% of [Max])	3%
Readability coating thickness [d] (µm)	0,1 µm; 1 µm
Measuring range coating thickness [d] (µm)	100 µm; 1250 µm
Offset accur (% of [Max])	1%
Sensor placement position	internal
Coating thickness gauge sensor type	FE NFE
Test object thickness coating	Non-magnetic coatings on iron, steel, Type F Coatings on non-magnetic metals, type N
Smallest sample, flat [radius]	13 mm
Smallest sample, concave [radius]	80 mm
Smallest sample, convex [radius]	1,5 mm

## Approval

CE mark ✓

## Display

Display type LCD

# KERN TC 1250-0.1FN

Robust coating thickness gauge – compact and easy to use



## Pictograms

### STANDARD



### OPTION

