KERN CCS 3T-3



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Catagony	
Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS
Measuring System	
Reference scale - item number	CFS 6K0.1
Quantity scale - Item number	KIP 3000V20M
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	6 kg
Quantity scale - Weighing capacity [Max]	3000 kg
Reference scale - Readability [d]	100 mg
Quantity scale - Readability [d]	1 kg
Linearity	±
Reference scale - Linearity	200 mg
Quantity scale - Linearity	2 kg
Reproducibility	0,0002 kg
Reference scale - Reproducibility	100 mg
Quantity scale - Reproducibility	1 kg
Default unit	kg
Units	kg Ib
Adjustment options	Adjusting with external weight
Recommended adjusting weight	3000 kg (M1)
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,0005 kg
Reference scale - Eccentric loading at 1/3 [Max]	500 mg
Quantity scale - Eccentric loading at 1/3 [Max]	2 kg

Approval	
CE mark	1
Display	
Display type	LCD
Display backlight	1
Display digit height	20 mm
Construction	
Dimension housing (W×D×H)	320×350×125 mm
Dimensions weighing platform (W×D×H)	1200×1500×108 mm
Material housing	plastic
Material weighing plate	coated metal
Dimensions weighing surface (W×D)	1200×1500 mm
Cable length	1,5 m
Display device cable length	5 m
Material load cell(s)	aluminium
Levelling feet adjustable	\checkmark
Functions	
Auto-off interval(s) in battery	
mode/rechargeable battery mode	selectable
mode/rechargeable battery mode PreTare function	selectable
PreTare function	1
PreTare function Tare function	✓ manual (multi)
PreTare function Tare function Counting function	✓ manual (multi) ✓ ✓
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total)
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total	✓ manual (multi) ✓ ✓ Rez A (Net total) 100
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ KS-232 standard IP23 IP65
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ KS-232 standard IP23 IP65
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ KS-232 standard IP23 IP65
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform Counting Smallest piece weight when piece	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ ✓ RS-232 standard IP23 IP65 IP65
PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform Counting Smallest piece weight when piece counting - laboratory conditions	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23 IP65 IP65 IP65

KERN CCS 3T-3



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Counting resolution (laboratory conditions) 30.000.000

Power Supply	
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO CH
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	70 h
Rechargeable battery operating time - backlight off	60 h
Battery / accumulator type	Pb

Pictograms

STANDARD





OPTION



Environmental conditions

Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 ° C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	4 d
Dimensions packaging (W×D×H)	1270×1560×240 mm
Net weight	110 kg
Shipping method	Freight
Net weight approx.	110 kg
Gross weight approx.	115 kg
Shipping weight	115 kg

Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/ Max depends on resolution and capacity
Article number for DAkkS calibration	962-132-128
Article number for certificate of conformity (verification)	969-517