
# KERN CCS 600K-1



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



<u></u>	
Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS
Measuring System	
Reference scale - item number	CFS 6K0.1
Quantity scale - Item number	KIP 600V20M
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	6 kg
Quantity scale - Weighing capacity [Max]	600 kg
Reference scale - Readability [d]	100 mg
Quantity scale - Readability [d]	0,2 kg
Linearity	±
Reference scale - Linearity	200 mg
Quantity scale - Linearity	0,4 kg
Reproducibility	0,0002 kg
Reference scale - Reproducibility	100 mg
Quantity scale - Reproducibility	0,2 kg
Default unit	kg
Units	kg Ib
Adjustment options	Adjusting with external weight
Recommended adjusting weight	600 kg (M1)
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,0005 kg
Reference scale - Eccentric loading at 1/3 [Max]	500 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,4 kg

Approval	
Approval	,
CE mark	✓
Display	
Display type	LCD
Display backlight	$\checkmark$
Display digit height	20 mm
Construction	
Dimension housing (W×D×H)	320×350×125 mm
Dimensions weighing platform (W×D×H)	1200×1500×108 mm
Material housing	plastic
Material weighing plate	coated metal
Dimensions weighing surface (W×D)	1200×1500 mm
Cable length	1,5 m
Display device cable length	5 m
Material load cell(s)	aluminium
Levelling feet adjustable	1
Functions	
Auto-off interval(s) in battery	
mode/rechargeable battery mode	selectable
mode/rechargeable battery mode PreTare function	1
mode/rechargeable battery mode PreTare function Tare function	✓ manual (multi)
mode/rechargeable battery mode PreTare function Tare function Counting function	✓ manual (multi) ✓
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing	✓ manual (multi) ✓
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function	✓ manual (multi) ✓ ✓
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level	✓ manual (multi) ✓ ✓ Rez A (Net total)
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total	✓ manual (multi) ✓ ✓ Rez A (Net total) 100
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function	✓ manual (multi) ✓ ✓ Rez A (Net total)
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23 IP65
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23 IP65
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform <b>Counting</b> Smallest piece weight when piece	✓ manual (multi) ✓ ✓ Rez A (Net total) 100 ✓ ✓ KS-232 standard IP23 IP65 IP65
mode/rechargeable battery mode PreTare function Tare function Counting function Tolerance weighing Conversion function Recipe/summing level PLU - total Sum memory function Memory function Interfaces IP protection - display IP protection - load cell IP protection - platform <b>Counting</b> Smallest piece weight when piece counting - laboratory conditions	✓ manual (multi) ✓ ✓ ✓ Rez A (Net total) 100 ✓ ✓ RS-232 standard IP23 IP65 IP65 IP65

# KERN CCS 600K-1



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999


Counting resolution (laboratory conditions)

Power Supply	
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO CH
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	70 h
Rechargeable battery operating time - backlight off	60 h
Battery / accumulator type	Pb

6.000.000

### Pictograms

#### STANDARD





#### OPTION



## Environmental conditions

Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

### Packing & Shipping

Readability force [d] (N)	4 d
Dimensions packaging (W×D×H)	1025×1025×235 mm
Net weight	110 kg
Shipping method	Freight
Net weight approx.	110 kg
Gross weight approx.	115 kg
Shipping weight	115 kg

#### Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/ Max   depends on resolution and capacity
Article number for DAkkS calibration	962-130-127
Article number for certificate of conformity (verification)	969-517