
KERN CCS 600K-1S



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Category	
Brand	KERN
Product categoriy	Industrial scale
Product group	Counting system
Product family	CCS
Measuring System	
Reference scale - item number	CFS 6K0.1
Quantity scale - Item number	KIP 600V20SM
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	6 kg
Quantity scale - Weighing capacity [Max]	600 kg
Reference scale - Readability [d]	100 mg
Quantity scale - Readability [d]	0,2 kg
Linearity	±
Reference scale - Linearity	200 mg
Quantity scale - Linearity	0,4 kg
Reproducibility	0,0002 kg
Reference scale - Reproducibility	100 mg
Quantity scale - Reproducibility	0,2 kg
Default unit	kg
Units	kg Ib
Adjustment options	Adjusting with external weight
Recommended adjusting weight	600 kg (M1)
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,0005 kg
Reference scale - Eccentric loading at 1/3 [Max]	500 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,4 kg

Approval CE mark Display
Display
Display
Display type LCD
Display backlight
Display digit height 20 mm
Construction
Dimension housing (W×D×H) 320×350×125 mm
Dimensions weighing platform (W×D×H) 1000×1000×108 mm
Material housing plastic
Material weighing plate coated metal
Dimensions weighing surface 1000×1000 mm (W×D)
Cable length 1,5 m
Display device cable length 5 m
Material load cell(s) aluminium
Levelling feet adjustable
Functions
Functions
Functions Auto-off interval(s) in battery mode/rechargeable battery mode
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare functionTare functionmanual (multi)
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓Memory function✓InterfacesRS-232 standard
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare functionTare functionmanual (multi)Counting functionTolerance weighingConversion functionRecipe/summing levelRez A (Net total)PLU - total100Sum memory functionMemory functionInterfacesRS-232 standardIP protection - displayIP23
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓InterfacesRS-232 standardIP protection - displayIP65
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓Memory function✓InterfacesRS-232 standardIP protection - displayIP23
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓InterfacesRS-232 standardIP protection - displayIP65
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓InterfacesRS-232 standardIP protection - displayIP23IP protection - platformIP65
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓InterfacesRS-232 standardIP protection - displayIP23IP protection - load cellIP65IP protection - platformI00 mgSmallest piece weight when piece counting - laboratory conditions100 mg
Auto-off interval(s) in battery mode/rechargeable battery modeselectablePreTare function✓Tare functionmanual (multi)Counting function✓Tolerance weighing✓Conversion function✓Recipe/summing levelRez A (Net total)PLU - total100Sum memory function✓InterfacesRS-232 standardIP protection - displayIP23IP protection - load cellIP65IP protection - platformIP65Smallest piece weight when piece counting - laboratory conditions100 mg

KERN CCS 600K-1S



Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

Counting resolution (laboratory conditions)

Power Supply	
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO CH
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	70 h
Rechargeable battery operating time - backlight off	60 h
Battery / accumulator type	Pb

6.000.000

Environmental conditions

Humity of environment [Min]	0 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	0 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping


Readability force [d] (N)	4 d
Dimensions packaging (W×D×H)	1050×1050×260 mm
Net weight	110 kg
Shipping method	Freight
Net weight approx.	110 kg
Gross weight approx.	115 kg
Shipping weight	115 kg

Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/ Max depends on resolution and capacity
Article number for DAkkS calibration	962-130-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD





OPTION

••	DAkkS
ACCU	+3 DAYS