

KERN CKE 16K0.1



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution 160.000 points



Category

Brand	KERN
Product category	Industrial scale
Product group	Counting scale
Product family	CKE

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	16 kg
Readability [d]	0,0001 kg
Resolution	160.000
Linearity	± 0,0003 kg
Reproducibility	0,0001 kg
Default unit	kg

Units	kg
	g
	gn
	dwt
	ozt
	lb
	oz
	ffa PCS

Adjustment options	Adjusting with external weight
Recommended adjusting weight	15 kg (F1)
Possible calibration points	5 kg; 10 kg; 15 kg
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,001 kg
Maximum creep (15 minutes)	1 g
Maximum creep (30 minutes)	2 g

Zulassung

CE mark	✓
---------	---

Display

Display type	LCD
Display screen size	120×38 mm
Display backlight	✓
Display segments	7
Display digit height	25 mm

Construction

Dimension housing (W×D×H)	350×390×120 mm
Dimensions weighing platform (W×D×H)	340×240×21 mm
Material display housing	Plastics
Material housing	ABS plastic
Material weighing plate	stainless steel
Dimensions weighing surface (W×D)	340×240 mm
Levelling feet adjustable	✓
Level indicator	✓

Functions

Number of keys for operation	7
Auto-off interval(s) in mains power mode	5 min
	2 min
	1 min
	30 min
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min
	2 min
	1 min
	30 min
	60 min 30 sec
PreTare function	✓
Tare function	manual (multi)
Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Underfloor weighing	Hook (included in delivery)
Interfaces	RS-232 (optional)
	Ethernet (optional)
	Bluetooth BLE (v4.0) (optional)
	USB-Device (optional)
	KUP WiFi (optional)

KERN CKE 16K0.1



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution 160.000 points

Counting

Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Counting reference weight can be entered	✓
Reference quantity	5, 10, 20, 50, n (any number of pieces)
Counting resolution (laboratory conditions)	160.000

Power Supply

Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Input voltage device / power [Max]	5,9V, 1A
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	8 h
Rechargeable battery operating time - backlight on	24 h
Rechargeable battery operating time - backlight off	48 h
Battery	4×1.5 V AA
Battery / accumulator type	Li-Ion
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Max]	80 %

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	470×470×190 mm
Net weight	6,5 kg
Shipping method	Parcel service

Net weight approx.	7 kg
Gross weight approx.	8 kg
Shipping weight	8,4 kg

Services (optional)

Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

