

KERN KDP 10K-3-2022e

KERN

Universal weighing platforms for flexible connection in process chains



Category	
Brand	KERN
Product category	Component
Product group	Digital platform
Product family	KDP

Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	10 kg
Readability [d]	1 g
Resolution	10.000
Linearity	± 3 g
Reproducibility	1 g
Default unit	g
Adjustment options	Adjusting with external weight
Recommended adjusting weight	10 kg (M1)
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	3 g
Maximum creep (15 minutes)	4 g
Maximum creep (30 minutes)	8 g

Approval	
CE mark	✓

Construction	
Dimension display device (W×D×H)	0×0×0 mm
Dimension housing (W×D×H)	165×166×75 mm
Dimensions weighing platform (W×D×H)	165×165×73 mm
Dimensions completely mounted (W×D×H)	165×166×75 mm

Material display housing	No display available
Material housing	plastic
Material weighing plate	stainless steel
Material platform	Plastics
Dimensions weighing surface (W×D)	160×160 mm
Cable length	1,2 m
Display device cable length	1,5 m
Levelling feet adjustable	✓

Functions	
Auto-off interval(s) in mains power mode	off
Interfaces	Ethernet (optional, factory) WiFi (optional, factory) Bluetooth BLE (v4.0) (optional, factory) USB-Device
IP protection - display	no IP protection

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	5 V, 1 A
Plug-in power supply type	USB including power supply
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH

Environmental conditions	
Humidity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	250×355×160 mm
Net weight	1,35 kg
Shipping method	Parcel service
Net weight approx.	1,4 kg
Gross weight approx.	2,2 kg
Shipping weight	2,8 kg

KERN KDP 10K-3-2022e



Universal weighing platforms for flexible connection in process chains

Services (optional)

Article number for adjustment at the location of installation	961-248
Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

