KERN MPE 200K-1HEM



High quality personal floor scale with BMI function - with approval for professional medical use in medical diagnostics, verification optional



Category

Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPE-E

Measuring System

Wedduring Oystern	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Resolution	2.500
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	249,9 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Measuring range measuring rod (cm)	90-100cm @ 0,1cm ± 0,5cm 100-205cm @ 0,1cm ± 1cm

1

Accuracy classe	III
Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	1
Approved as a medical device	1
Display	
Display type	LCD
Display backlight	✓
Display digit height - smallest digit	5 mm
Display digit height	25 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	200×55×128 mm
Dimensions weighing platform (W×D×H)	365×360×80 mm
Dimensions completely mounted (W×D×H)	365×570×2134 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	plastic
Dimensions weighing surface (W×D)	365×360 mm
Stand haight	0.40
Stand height	940 mm
Functions	940 mm
Functions	940 mm 7
-	
Functions	7
Functions Number of keys for operation	7 3 min 5 min 30 min
Functions Number of keys for operation Auto-off interval(s) in mains power	7 3 min 5 min 30 min 15 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode	7 3 min 5 min 30 min 15 min 3 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery	7 3 min 5 min 30 min 15 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode	7 3 min 5 min 30 min 15 min 3 min 5 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode Tare function	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min 15 min manual (single & multi)
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min manual (single & multi) ✓
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode Auto-off interval(s) in battery mode Tare function Hold function Function for averaging under unstable weighing conditions	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min 30 min 15 min manual (single & multi) ✓
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply /	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modeAuto-off interval(s) in battery mode/rechargeable battery modeTare functionHold functionFunction for averaging under unstable weighing conditionsFunction for BMI calculation InterfacesPower SupplyInput voltage power supply / power [Max]	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min 30 min 15 min manual (single & multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz
Functions Number of keys for operation Auto-off interval(s) in mains power mode Auto-off interval(s) in battery mode Auto-off interval(s) in battery mode / rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max]	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min 30 min 15 min 30 min 15 min 30 min 15 min manual (single & multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA
FunctionsNumber of keys for operationAuto-off interval(s) in mains power modeAuto-off interval(s) in battery mode/rechargeable battery modeAuto-off interval(s) in battery mode/rechargeable battery modeTare functionHold functionFunction for averaging under unstable weighing conditionsFunction for BMI calculation InterfacesPower SupplyInput voltage power supply / power [Max]	7 3 min 5 min 30 min 15 min 3 min 5 min 30 min 15 min 30 min 15 min manual (single & multi) ✓ ✓ KS-232 standard 100 V - 240 V, 50 / 60 Hz

Approval

CE mark

KERN MPE 200K-1HEM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional

Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery voltage	9 V
Battery operating time	20 h

Environmental conditions

Humity of environment [Min]	5 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	00 °C

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	1010×290×445 mm
Net weight	11,13 kg
Shipping method	Parcel service
Net weight approx.	12 kg
Gross weight approx.	14 kg
Shipping weight	26,1 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

