KERN OKM 173



The metallurgical reflected light microscope for material testing and surface testing, as well as quality assurance in industry



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Metallurgical microscope
Product family	OKM-1

Approval		
CE mark	✓	

Construction	
Dimension (W×D×H)	440×200×460 mm
Optical system	Infinity
Tube type	Siedentopf
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Nosepiece screw-in locations	4
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Contrasting methods	Bright field Polarisation (optional)
Light distribution	20:80
Interpupillary distance [Max]	75 mm
Interpupillary distance [Min]	50 mm
Camera - Adapter type	C-Mount
Supported camera types	Microscope Camera

HWF

10 x

High Eye Point

Ocular

Eye point

Ocular field width

Ocular magnifications

Ocular visual field	20 mm
Ocular diameter	23,2 mm
Focussing	
Fine drive minimum	0,002 mm
Torque regulation	✓
Field of view [Min]	0,45 mm
Field of view [Max]	3,6 mm
Focusing mechanism	coaxial coarse and fine drive
Illumination	
Illumination type incident light	LED
Illumination intensity incident light	5 W
Illumination type transmitted light	None
Illuminance	Reflected light
Aperture diaphragm	✓
Filter possible	√
The possible	•
Power Supply	
	100 V - 240 V AC 50/60
Power Supply Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO
Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO EURO UK
Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min]	100 V - 240 V AC 50/60 Hz 0,3 A 5 V, 1 A Power adapter Power supply unit EURO EURO UK

Readability force [d] (N)

Net weight

Shipping method

Shipping weight

Net weight approx.

Gross weight approx.

Dimensions packaging (W×D×H)

Objective	
Objectives - Details	Objective Infinity Plan 10 x / 0,25 LWD, antifungus
	1

1 d

7,66 kg

8 kg

10 kg

11,8 kg

Parcel service

550×375×285 mm

KERN OKM 173



The metallurgical reflected light microscope for material testing and surface testing, as well as quality assurance in industry

> Objective Infinity Plan 20 x / 0,4 LWD, anti-fungus Objective Infinity Plan 5 x / 0,13 LWD, antifungus Objective Infinity Plan 50 x / 0,75 spring, LWD, anti-fungus

Pictograms

STANDARD















