KERN OLM 170



The inverted metallurgical microscope for professional applications



| Category | |
|-------------------|--------------------------|
| Brand | Optics |
| Product categoriy | Microscope |
| Product group | Metallurgical microscope |
| Product family | OLM-1 |

| Approval | |
|----------|---|
| CE mark | ✓ |

| Construction | |
|-------------------------------|------------------------------|
| Dimension (W×D×H) | 470×240×330 mm |
| Optical system | Infinity |
| Tube type | Butterfly |
| Tube type | Trinocular |
| Tube angle of inclination | 45° |
| Lens quality | Infinity Plan |
| Standard objectives | 5× 10× 20× 50× |
| Nosepiece screw-in locations | 4 |
| Diopter adjustment | one-sided |
| Diopter adjustment [Min] | -6 |
| Diopter adjustment [Max] | 6 |
| Contrasting methods | Bright field Polarisation |
| Light distribution | 20:80 |
| Interpupillary distance [Max] | 75 mm |
| Interpupillary distance [Min] | 48 mm |

| Ocular | |
|--------------------|----------------|
| Ocular field width | HWF |
| Eye point | High Eye Point |

| Ocular magnifications | 10 x |
|-----------------------|---------|
| Ocular visual field | 20 mm |
| Ocular diameter | 23,2 mm |

| Focussing | |
|---------------------|-------------------------------|
| Fine drive minimum | 0,002 mm |
| Torque regulation | ✓ |
| Field of view [Min] | 0,4 mm |
| Field of view [Max] | 4 mm |
| Focusing mechanism | coaxial coarse and fine drive |

| Illumination | |
|---------------------------------------|-----------------|
| Illumination type incident light | LED |
| Illumination intensity incident light | 5 W |
| Illuminance | Reflected light |
| Illumination dimmable | Incident light |
| Filter possible | ✓ |

| Power Supply | |
|---|------------------------------|
| Input voltage power supply / power [Max] | 100 V - 240 V, 50 / 60 Hz |
| Input voltage device / power [Max] | 5 V, 1 A |
| Plug-in power supply type | Power adapter |
| Supplied power supply | Power supply unit |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| Plug-in power supply / adapter for countries - optional | EURO UK |

| Environmental conditions | |
|---------------------------|-------|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |
| Packing & Shipping | |

| Packing & Shipping | |
|------------------------------|----------------|
| Readability force [d] (N) | 1 d |
| Dimensions packaging (W×D×H) | 500×420×300 mm |
| Net weight | 6,506 kg |
| Shipping method | Parcel service |
| Net weight approx. | 7 kg |
| Gross weight approx. | 9 kg |
| Shipping weight | 12,6 kg |

| Objective | |
|----------------------|---|
| Objectives - Details | Objective Infinity Plan 10 x / 0,25 LWD, antifungus |

1

KERN OLM 170



The inverted metallurgical microscope for professional applications

Objective Infinity Plan 20 x / 0,4 LWD, anti-fungus Objective Infinity Plan 5 x / 0,13 LWD, antifungus Objective Infinity Plan 50 x / 0,75 spring, LWD, anti-fungus

Pictograms

STANDARD















