## KERN OZL 474



The flexible, affordable all-rounder with flexible incident illumination for training workshops, inspection authorities and laboratories



| Category                      |                   |
|-------------------------------|-------------------|
| Brand                         | Optics            |
| Product categoriy             | Microscope        |
| Product group                 | Stereo microscope |
| Product family                | OZL-47            |
| Approval                      |                   |
| CE mark                       | ✓                 |
| Construction                  |                   |
| Dimension (W×D×H)             | 300×240×420 mm    |
| Optical system                | Greenough         |
| Tube type                     | Trinocular        |
| Tube angle of inclination     | 45°               |
| Tube 360° rotation            | $\checkmark$      |
| Eyepieces fixed               | $\checkmark$      |
| Diopter adjustment            | both-sided        |
| Diopter adjustment [Min]      | -5                |
| Diopter adjustment [Max]      | 5                 |
| Contrasting methods           | Bright field      |
| Light distribution            | 100:0             |
| Interpupillary distance [Max] | 75 mm             |
| Interpupillary distance [Min] | 55 mm             |

## Ocular

| Ocular field width    | HWF            |
|-----------------------|----------------|
| Eye point             | High Eye Point |
| Ocular magnifications | 10 x           |
| Ocular visual field   | 20 mm          |
| Ocular diameter       | 30 mm          |

| Focussing                             |                 |
|---------------------------------------|-----------------|
| Torque regulation                     | 1               |
| Working distance                      | 105 mm          |
| Zoom [Min]                            | 0,7 x           |
| Zoom [Max]                            | 4,5 x           |
| Magnification ratio                   | 6,4:1           |
| Field of view [Min]                   | 4,4 mm          |
| Field of view [Max]                   | 28,6 mm         |
| Focusing mechanism                    | coarse drive    |
| Standard total magnification [Min]    | 7 x             |
| Standard total magnification [Max]    | 45 x            |
|                                       |                 |
| Illumination                          |                 |
| Illumination type incident light      | LED             |
| Illumination intensity incident light | 3 W             |
| Illuminance                           | Reflected light |
| Illumination dimmable                 | Incident light  |
|                                       |                 |
| Power Supply                          |                 |
| Plug-in power supply / adapter for    | UK              |
| countries - optional                  |                 |
| Environmental conditions              |                 |
| Environmental conditions              |                 |
| Storage temperature [Min]             | -5 °C           |
| Storage temperature [Max]             | 40 °C           |
|                                       |                 |
| Packing & Shipping                    |                 |
| Readability force [d] (N)             | 1 d             |
| Dimensions packaging (W×D×H)          | 452×414×290 mm  |
| Net weight                            | 4,085 kg        |
| Shipping method                       | Parcel service  |
| Net weight approx.                    | 4,2 kg          |
| Gross weight approx.                  | 7 kg            |
| Shipping weight                       | 10,9 kg         |
|                                       |                 |
| Pictograms                            |                 |
|                                       |                 |

## STANDARD

