


Precision Balances KERN PES · PEJ



## Robust laboratory and industrial precision scale for heavy items, verification optional

### Features

- KERN PEJ: Automatic internal adjustment, guarantees high degree of accuracy and makes the balance independent of its location of use
- KERN PES: Adjusting program CAL for quick setting of the balance accuracy using an external test weight at an additional price, see *Test Weights*
- Metal housing: robust and sturdy
- Weighing with tolerance range (checkweighing): Input of two upper and two lower limit values through four arrow keys. An audible and visual signal assists with the portioning, dispensing or grading
- Draught shield standard for models with weighing plate size **A**, weighing space W×D×H 170×150×100 mm
- **A**, **B** Underfloor weighing: load support with hook on the underside of the balance for models

- **A** Hook included with the delivery
- **B** Hook not included with the delivery
- **A**, **B**: Protective working cover included with delivery


### Technical data

- Fluorescent display, bright with high contrast, digit height 14 mm
- Dimensions weighing surface, stainless steel
  - A** W×D 140×120 mm
  - B** W×D 200×200 mm, see larger picture
  - C** W×D 250×220 mm
- Overall dimensions (without draught shield) W×D×H
  - A**, **B** 220×333×93 mm
  - C** 260×330×113 mm
- Permissible ambient temperature 10 °C/30 °C

### Accessories

- **A**, **B**: Protective working cover, scope of delivery: 5 items, KERN PES-A04S05
- KERN PES: Internal rechargeable battery pack, operating time up to 6 h with backlight, charging time approx. 15 h, KERN PES-A01
- Loop for underfloor weighing, for models with weighing plate size **B**, KERN PES-A03
- Relay output to connect relays, signal lamps, valves etc., 5 outputs for weighing in 3 tolerance ranges, must be ordered at purchase, KERN PES-A02
- Minimum weight of sample, smallest weight to be weighed, depending on the required process accuracy, only in combination with a DAkkS calibration certificate, KERN 969-103
- Equipment qualification: compliant qualification concept which includes the following validation services, Installation Qualification (IQ), Operating Qualification (OQ)
- Further details, plenty of further accessories and suitable printers see *Accessories*


### STANDARD



### OPTION






### FACTORY



Model	Weighing capacity [Max] g	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Linearity g	Weighing plate	Net weight kg	Options	
								Verification	DAkkS Calibr. Certificate
<b>KERN</b>								<b>M</b>	<b>KERN</b>
<b>PES 620-3M</b>	620	0,001	-	-	± 0,003	<b>A</b>	3,6	-	963-103
<b>PES 2200-2M</b>	2200	0,01	-	-	± 0,02	<b>B</b>	4,4	-	963-127
<b>PES 4200-2M</b>	4200	0,01	-	-	± 0,02	<b>B</b>	4,0	-	963-127
<b>PES 6200-2M</b>	6200	0,01	-	-	± 0,03	<b>B</b>	4,4	-	963-104
<b>PES 15000-1M</b>	15000	0,1	-	-	± 0,2	<b>B</b>	4,4	-	963-128
<b>PES 31000-1M</b>	31000	0,1	-	-	± 0,4	<b>C</b>	10,0	-	963-128

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

<b>PEJ 620-3M</b>	620	0,001	0,01	0,1	± 0,003	<b>A</b>	4,4	965-201	963-103
<b>PEJ 4200-2M</b>	4200	0,01	0,1	0,5	± 0,02	<b>B</b>	6,0	965-216	963-127
<b>PEJ 2200-2M</b>	2200	0,01	0,1	0,5	± 0,02	<b>B</b>	6,0	965-216	963-127

 <p><b>Internal adjusting</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)</p>	 <p><b>Interface for second balance</b> For direct connection of a second balance</p>	 <p><b>Hold function</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value</p>	 <p><b>Conformity Assessment</b> The time required for conformity assessment is specified in the pictogram</p>
 <p><b>Adjusting program CAL</b> For quick setting up of the balance's accuracy. External adjusting weight required</p>	 <p><b>Network interface</b> For connecting the scale to an Ethernet network</p>	 <p><b>Protection against dust and water splashes IPxx</b> The type of protection is shown in the pictogram</p>	 <p><b>DAkkS calibration possible (DKD)</b> The time required for DAkkS calibration is shown in days in the pictogram</p>
 <p><b>EasyTouch</b> Suitable for the connection, data transmission and control through PC or tablet</p>	 <p><b>KERN Communication Protocol (KCP)</b> It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p>	 <p><b>Suspended weighing</b> Load support with hook on the underside of the balance</p>	 <p><b>Factory calibration (ISO)</b> The time required for Factory calibration is shown in days in the pictogram</p>
 <p><b>Memory</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.</p>	 <p><b>GLP/ISO log intern</b> The balance displays weight, date and time, independent of a printer connection</p>	 <p><b>Battery operation</b> Ready for battery operation. The battery type is specified for each device</p>	 <p><b>Package shipment</b> The time required for internal shipping preparations is shown in days in the pictogram</p>
 <p><b>Alibi memory</b> Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.</p>	 <p><b>GLP/ISO log Printer</b> With weight, date and time. Only with KERN printers.</p>	 <p><b>Rechargeable battery pack</b> Rechargeable set</p>	 <p><b>Pallet shipment</b> The time required for internal shipping preparations is shown in days in the pictogram</p>
 <p><b>KERN Universal Port (KUP)</b> allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort</p>	 <p><b>GLP/ISO log intern</b> The balance displays weight, date and time, independent of a printer connection</p>	 <p><b>Universal plug-in power supply</b> with universal input and optional input socket adapters for A) EU, CH, GB B) EU, CH, GB, US C) EU, CH, GB, US, AUS</p>	
 <p><b>RS-232 Data interface</b> To connect the balance to a printer, PC or network</p>	 <p><b>Piece counting</b> Reference quantities selectable. Display can be switched from piece to weight</p>	 <p><b>Plug-in power supply</b> 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available</p>	
 <p><b>RS-485 Data interface</b> To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible</p>	 <p><b>Recipe level A</b> The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out</p>	 <p><b>Integrated power supply unit</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request</p>	
 <p><b>USB Data interface</b> To connect the balance to a printer, PC or other peripherals</p>	 <p><b>Recipe level B</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display</p>	 <p><b>Weighing principle Strain gauges</b> Electrical resistor on an elastic deforming body</p>	
 <p><b>Bluetooth* Data interface</b> To transfer data from the balance to a printer, PC or other peripherals</p>	 <p><b>Totalising level A</b> The weights of similar items can be added together and the total can be printed out</p>	 <p><b>Weighing principle Tuning fork</b> A resonating body is electromagnetically excited, causing it to oscillate</p>	
 <p><b>WIFI Data interface</b> To transfer data from the balance to a printer, PC or other peripherals</p>	 <p><b>Percentage determination</b> Determining the deviation in % from the target value (100 %)</p>	 <p><b>Weighing principle Electromagnetic force compensation</b> Coil inside a permanent magnet. For the most accurate weighings</p>	
 <p><b>Control outputs</b> (optocoupler, digital I/O) To connect relays, signal lamps, valves, etc.</p>	 <p><b>Weighing units</b> Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details</p>	 <p><b>Weighing principle Single cell technology</b> Advanced version of the force compensation principle with the highest level of precision</p>	
 <p><b>Analogue interface</b> to connect a suitable peripheral device for analogue processing of the measurements</p>	 <p><b>Weighing with tolerance range (Checkweighing)</b> Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model</p>		

\* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.