

# KERN PLJ 720-3A

Range of precision balances with enormous weighing capacities – ideal for heavy tare containers or large samples



Automatic adjustment - Standard temperature deviation	1,2 °C
---	--------

Stabilization time	2 s
--------------------	-----

Warm-up time	4 h
--------------	-----

Eccentric loading at 1/3 [Max]	0,004 g
--------------------------------	---------

Maximum creep (15 minutes)	10 mg
----------------------------	-------

Maximum creep (30 minutes)	20 mg
----------------------------	-------

## Approval

CE mark	✓
---------	---

## Display

Display type	LCD graphic
--------------	-------------

Display screen size	132×38 mm
---------------------	-----------

Display backlight	✓
-------------------	---

Display digit height - smallest digit	4 mm
---------------------------------------	------

Display digit height	15 mm
----------------------	-------

Languages of the user interface	English
---------------------------------	---------

## Construction

Dimension housing (W×D×H)	210×340×120 mm
---------------------------	----------------

Dimensions ring-shaped draught shield - inner (Ø×H)	150×60 mm
---	-----------

Dimensions ring-shaped draught shield - outer (Ø×H)	160×70 mm
---	-----------

Dimensions completely mounted (W×D×H)	210×340×160 mm
---------------------------------------	----------------

Material housing	plastic
------------------	---------

Material weighing plate	stainless steel
-------------------------	-----------------

Material platform	Stainless steel
-------------------	-----------------

Material draught shield	glass
-------------------------	-------

Dimensions weighing surface (Ø)	110 mm
---------------------------------	--------

Transport safety lock - bolt torque	0,1 Nm
-------------------------------------	--------

Levelling feet adjustable	✓
---------------------------	---

## Functions

Number of keys for operation	6
------------------------------	---

	off
--	-----

Auto-off interval(s) in mains power mode	5 min
--	-------

	2 min
--	-------

	15 min
--	--------

Capacity - Display	✓
--------------------	---

Time display	✓
--------------	---

PreTare function	✓
------------------	---

Tare function	manual (multi)
---------------	----------------

Density determination	✓
-----------------------	---

Percentage determination	✓
--------------------------	---

Counting function	✓
-------------------	---

## Category

Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PLJ

## Measuring System

Construction type of the scale	Single-range balance
Weighing system	Force compensation
Weighing capacity [Max]	720 g
Weighing capacity [Max] (ct)	3600 ct
Readability [d]	0,001 g
Resolution	720.000
Linearity	± 0,002 g
Reproducibility	0,001 g
Tare range	720 g
Default unit	g

Units	g
	mg
	gn
	dwt
	tl (Tw)
	tl (HK)
	ozt
	tl (Singap, Malays)
	ct
	mo
lb	
oz	

USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
--	-----

Adjustment options	Internal calibration (automatic)
--------------------	----------------------------------

# KERN PLJ 720-3A



Range of precision balances with enormous weighing capacities – ideal for heavy tare containers or large samples

Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Function for averaging under unstable weighing conditions	✓
Standby function	✓
Recipe/summing level	Rez B (Net-total, memory with plain text designations + setpoint, also for printout)
Recipe weighing - number of database entries	99
Recipe weighing - number of ingredients per database entry	20
Underfloor weighing	Eye (included in delivery)
Interfaces	RS-232 standard

## Counting

Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Counting reference weight can be entered	✓
Reference quantity	10, 25, 50, 100, n (any number of pieces)
Counting resolution (laboratory conditions)	720.000

## Power Supply

Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	24 V 1 A
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH

## Environmental conditions

Humidity of environment [Max]	80 %
Ambient temperature [Min]	15 °C
Ambient temperature [Max]	35 °C
Storage temperature [Max]	40 °C

## Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	500×360×420 mm
Net weight	4,9 kg
Shipping method	Parcel service
Net weight approx.	5,0 kg
Gross weight approx.	8 kg
Shipping weight	15,1 kg

## Services (optional)

Article number for DAkkS calibration	963-103
Article number for certificate of conformity (verification)	969-517

## Pictograms

### STANDARD



### OPTION

