

KERN PWS 3000-1

KERN

High-resolution precision balance made of stainless steel with IP protection



Category

Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PWS

Measuring System

Construction type of the scale	Single-range balance
Number of weighing ranges	1
Weighing system	Tuning fork
Weighing capacity [Max]	3200 g
Readability [d]	0,1 g
Resolution	32.000
Linearity	± 0,1 g
Reproducibility	0,1 g
Tare range	3200 g
Default unit	g

Units	kg
	g
	gn
	dwt
	tl (Tw)
	tl (HK)
	ozt
	tl (Singap, Malays)
	ct
	mo
	lb
	oz
	tol

USP Minimum weight of sample (k = 2, U = 0.1%) 200 g

Adjustment options Adjusting with external weight

Recommended adjusting weight	3 kg (F1)
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,3 g
Maximum creep (15 minutes)	400 mg
Maximum creep (30 minutes)	800 mg

Zulassung

CE mark ✓

Display

Display type	LCD
Display screen size	109×27 mm
Display backlight	✓
Display digit height	16,5 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	310×205×85 mm
Dimensions completely mounted (W×D×H)	320×205×90 mm
Material housing	stainless steel
Material weighing plate	stainless steel
Material platform	Stainless steel
Dimensions weighing surface (W×D)	190×190 mm
Levelling feet adjustable	✓
Level indicator	✓

Functions

Number of keys for operation	9
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Capacity - Display	✓
PreTare function	✓
Tare function	manual (multi)
Density determination	✓
Percentage determination	✓
Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Function for averaging under unstable weighing conditions	✓
Recipe/summing level	Rez A (Net total)
Underfloor weighing	Eye (optional)
Interfaces	RS-232 standard
IP protection - complete device	IP65

KERN PWS 3000-1



High-resolution precision balance made of stainless steel with IP protection

Counting

Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Counting reference weight can be entered	✓
Reference quantity	5, 10, 30, 100
Counting resolution (laboratory conditions)	32.000

Power Supply

Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage device / power [Max]	5,95 V, 1 A
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Battery	4×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert

Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping


Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	315×405×225 mm
Net weight	2,808 kg
Shipping method	Parcel service
Net weight approx.	3,0 kg
Gross weight approx.	4,2 kg
Shipping weight	5,7 kg

Services (optional)

Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

