

# KERN UIB 600K-1

Pallet scale with steel load support (IP67) and the best price-to-performance ratio



Display	
Display type	LCD
Display backlight	✓
Display digit height	25 mm

Construction	
Dimension display device (W×D×H)	235×114×51 mm
Dimensions weighing platform (W×D×H)	1195×840×110 mm
Material display housing	Plastics
Material weighing plate	steel, powder-coated
Material platform	steel, powder-coated
Dimensions weighing surface (W×D)	1195×840 mm
Cable length	5 m
Display device cable length	5 m
Allowed cable length display device [Max]	15 m
Load cells - number	4
Levelling feet adjustable	✓
Wall mount	✓
Stand inclinable	✓

Functions	
Number of keys for operation	4
Auto-off interval(s) in mains power mode	selectable
Tare function	manual (single)
Hold function	✓
Underfloor weighing	None
IP protection - load cell	IP67

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0,3 A
Input voltage device / power [Max]	9 V, 100 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH

Plug-in power supply / adapter for countries - optional	EURO AUS UK US
---	-------------------------

Category	
Brand	KERN
Product category	Industrial scale
Product group	Pallet scale
Product family	UIB

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	600 kg
Readability [d]	0,2 kg
Resolution	3.000
Linearity	± 0,6 kg
Reproducibility	0,2 kg
Tare range	-600 kg
Default unit	kg
Units	kg lb
Adjustment options	Adjusting with external weight
Stabilization time	4 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	1 kg
Maximum creep (15 minutes)	800 g
Maximum creep (30 minutes)	1,6 kg
Loadcell type	KELI SQB
Load cell connection	4-wire

Approval	
CE mark	✓

# KERN UIB 600K-1



Pallet scale with steel load support (IP67) and the best price-to-performance ratio

Battery	4×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery operating time	60 h

## Environmental conditions

Humidity of environment [Min]	10 %
Humidity of environment [Max]	95 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C

## Packing & Shipping

Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	1270×900×260 mm
Net weight	51 kg
Shipping method	Freight
Net weight approx.	55 kg
Gross weight approx.	90 kg
Shipping weight	87 kg

## Services (optional)

Article number for adjustment at the location of installation	961-250
Article number for DAkkS calibration	963-130
Article number for certificate of conformity (verification)	969-517

## Pictograms

### STANDARD



### OPTION

